SAFETY DATA SHEET

1. Identification

Product identifier PW, AG716, AG916

Other means of identification

Synonyms Polymer Wet Coat

Recommended use Polish.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer/Supplier Granitize Products, Inc.

11022 Vulcan Street

South Gate, CA 90280-0893 US

Telephone: (562) 923-5438

Emergency CHEMTREC: (800) 424-9300

CHEMTREC International: 00 1-703-527-3887

2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 4Health hazardsSkin corrosion/irritationCategory 2Serious eye damage/eye irritationCategory 2A

Reproductive toxicity Category 2
Specific target organ toxicity, repeated Category 1 (Central nervous system)

exposure

Environmental hazards Hazardous to the aquatic environment, acute Category 3

hazard

Hazardous to the aquatic environment,

long-term hazard

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Combustible liquid. Causes skin irritation. Causes serious eye irritation. Suspected of damaging

fertility or the unborn child. Causes damage to organs (Central nervous system) through

prolonged or repeated exposure. Harmful to aquatic life with long lasting effects.

Precautionary statement

PreventionObtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from flames and hot surfaces-No smoking. Do not breathe mist or

vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face

Category 3

protection.

Response If on skin: Wash with plenty of water. If in eyes: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use water fog, alcohol resistant foam, dry chemical powder, carbon dioxide (CO2)

to extinguish.

Storage Store in a well-ventilated place. Keep cool. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

None known.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%	
Water	7732-18-5	61 10	
Distillates (petroleum), hydrotreated light	64742-47-8		
Carnauba wax	8015-86-9	3.5	
Cyclomethicone	556-67-2	3	
Dimethoxysilyl ethylenediaminopropyl dimethicone	71750-80-6	3	
Metakaolin	66402-68-4	3	
Naphtha (petroleum), hydrodesulphurised heavy	64742-82-1	3	
Stoddard Solvent	8052-41-3	3	
2-Propanol	67-63-0	2	
Amorphous silica	61790-53-2	2	
Cyclopentasiloxane	541-02-6	1	
Polyalkyl siloxane	63148-62-9	1	
1,2,4-Trimethylbenzene	95-63-6	0.5	
Morpholine	110-91-8	0.5	
Oleic acid	112-80-1	0.5	

Composition comments

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact

Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical attention if

symptoms occur.

Most important

symptoms/effects, acute and delayed

Narcosis. Behavioral changes. Decrease in motor functions. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media

Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).

SDS US 2 / 10 936244 Version #: 02

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved.

Specific methods
General fire hazards

Use standard firefighting procedures and consider the hazards of other involved materials.

Combustible liquid.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Use water spray to reduce vapors or divert vapor cloud drift. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from open flames, hot surfaces and sources of ignition. Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat and sources of ignition. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	
2-Propanol (CAS 67-63-0)	PEL	980 mg/m3	
		400 ppm	
Naphtha (petroleum), hydrodesulphurised heavy (CAS 64742-82-1)	PEL	2900 mg/m3	
		500 ppm	
Stoddard Solvent (CAS 8052-41-3)	PEL	2900 mg/m3	
		500 ppm	

US. OSHA Table Z-3 (29 CFR 1910.10 Components	Туре	Value	
Amorphous silica (CAS 61790-53-2)	TWA	0.8 mg/m3	
		20 mppcf	
US. ACGIH Threshold Limit Values			
Components	Туре	Value	
2-Propanol (CAS 67-63-0)	STEL	400 ppm	
	TWA	200 ppm	
Naphtha (petroleum), hydrodesulphurised heavy (CAS 64742-82-1)	TWA	100 ppm	
Stoddard Solvent (CAS 8052-41-3)	TWA	100 ppm	
US. NIOSH: Pocket Guide to Chemic	al Hazards		
Components	Туре	Value	
2-Propanol (CAS 67-63-0)	STEL	1225 mg/m3	
		500 ppm	
	TWA	980 mg/m3	
		400 ppm	
Amorphous silica (CAS 61790-53-2)	TWA	6 mg/m3	
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)	TWA	100 mg/m3	
Naphtha (petroleum), hydrodesulphurised heavy (CAS 64742-82-1)	Ceiling	1800 mg/m3	
,	TWA	350 mg/m3	
Stoddard Solvent (CAS 8052-41-3)	Ceiling	1800 mg/m3	
	TWA	350 mg/m3	
US. Workplace Environmental Expos	ure Level (WEEL) Guides		
Components	Туре	Value	
Cyclomethicone (CAS 556-67-2)	TWA	10 ppm	
Cyclopentasiloxane (CAS 541-02-6)	TWA	10 ppm	

Bio

Components	Value	Determinant	Specimen	Sampling Time	
2-Propanol (CAS 67-63-0)	40 ma/l	Acetone	Urine	*	

^{* -} For sampling details, please see the source document.

Exposure guidelines No exposure standards allocated.

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide easy access to water supply and eye wash facilities.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

SDS US PW-C, AG-716, AG916

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Skin protection

Other Wear appropriate chemical resistant clothing.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not

been established), an approved respirator must be worn.

Thermal hazards When material is heated, wear gloves to protect against thermal burns.

General hygiene considerations

Observe any medical surveillance requirements. Avoid contact with eyes. Avoid contact with skin. When using, do not eat, drink or smoke. Provide eyewash station and safety shower. Handle in accordance with good industrial hygiene and safety practice. Routinely wash work clothing and

protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid. Form Liquid.

Color Not available.

Odor Aromatic.

Odor threshold Not available.

PH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling Not available.

range

Flash point 194.0 °F (90.0 °C) Closed Cup

Evaporation rate Not available.
Flammability (solid, gas) Not applicable.
Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

Explosive properties Not explosive. **Oxidizing properties** Not oxidizing.

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Heat, flames and sparks. Contact with incompatible materials. Avoid temperatures exceeding the

flash point. Protect against direct sunlight.

Incompatible materials Strong oxidizers, strong acids, and strong bases.

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Prolonged inhalation may be harmful. Inhalation

Skin contact Causes skin irritation.

Eye contact Causes serious eye irritation.

Ingestion May cause discomfort if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics Narcosis. Behavioral changes. Decrease in motor functions. Severe eve irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness

and pain. Prolonged exposure may cause chronic effects.

Information on toxicological effects

Not expected to be acutely toxic. **Acute toxicity**

Test Results Components **Species**

2-Propanol (CAS 67-63-0)

Acute

Dermal

LD50 Rabbit 16.4 ml/kg, 24 Hours

Inhalation

LC50 Rat > 10000 ppm, 6 Hours

Oral

Rat LD50 5.84 g/kg

Polyalkyl siloxane (CAS 63148-62-9)

Acute Dermal

Rabbit LD50 > 5000 mg/kg

Oral

LD50 Rat > 17000 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Amorphous silica (CAS 61790-53-2) 3 Not classifiable as to carcinogenicity to humans. 3 Not classifiable as to carcinogenicity to humans.

Naphtha (petroleum), hydrodesulphurised heavy (CAS

64742-82-1) Stoddard Solvent (CAS 8052-41-3) 3 Not classifiable as to carcinogenicity to humans.

NTP Report on Carcinogens

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not regulated.

Possible reproductive hazard. Suspected of damaging fertility or the unborn child. Reproductive toxicity

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Causes damage to organs (Central nervous system) through prolonged or repeated exposure.

Not an aspiration hazard. **Aspiration hazard**

Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Components **Species Test Results**

Cyclomethicone (CAS 556-67-2)

Aquatic

LC50 Fish > 1000 mg/l, 96 Hours Bluegill (Lepomis macrochirus)

Distillates (petroleum), hydrotreated light (CAS 64742-47-8)

Aquatic

Fish LC50 Rainbow trout, donaldson trout 2.9 mg/l, 96 hours

(Oncorhynchus mykiss)

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

0.05 2-Propanol (CAS 67-63-0) Cyclopentasiloxane (CAS 541-02-6) 5.2 Naphtha (petroleum), hydrodesulphurised heavy (CAS 3.16 - 7.15 64742-82-1)

Stoddard Solvent (CAS 8052-41-3) 3.16 - 7.15

Mobility in soil No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

potential.

13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow **Disposal instructions**

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Dispose in accordance with all applicable regulations. Local disposal regulations

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

NA1993 **UN** number

UN proper shipping name Transport hazard class(es) Combustible liquid, n.o.s. (Cyclomethicone, Stoddard Solvent)

- Combustible Liquid Class

Subsidiary risk Ш Packing group

Environmental hazards

Marine pollutant No

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions IB3,T1, T4, TP1

Packaging exceptions 150 203 Packaging non bulk Packaging bulk 241

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

PW-C, AG-716, AG916 SDS US 7 / 10

936244 Version #: 02 Revision date: 02-August-2018 Issue date: 03-February-2017 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Cyclomethicone (CAS 556-67-2)

1.0 % One-Time Export Notification only.

One-Time Export Notification only.

CERCLA Hazardous Substance List (40 CFR 302.4)

2-Propanol (CAS 67-63-0)

Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

Classified hazard

Flammable (gases, aerosols, liquids, or solids)

categories

Serious eye damage or eye irritation

Reproductive toxicity

Skin corrosion or irritation

Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

 Chemical name
 CAS number
 % by wt.

 2-Propanol
 67-63-0
 2

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

2-Propanol (CAS 67-63-0) Low priority

US state regulations

US. Massachusetts RTK - Substance List

2-Propanol (CAS 67-63-0)

Amorphous silica (CAS 61790-53-2)

Distillates (petroleum), hydrotreated light (CAS 64742-47-8)

Naphtha (petroleum), hydrodesulphurised heavy (CAS 64742-82-1)

Stoddard Solvent (CAS 8052-41-3)

US. New Jersey Worker and Community Right-to-Know Act

2-Propanol (CAS 67-63-0)

Distillates (petroleum), hydrotreated light (CAS 64742-47-8)

Naphtha (petroleum), hydrodesulphurised heavy (CAS 64742-82-1)

Stoddard Solvent (CAS 8052-41-3)

US. Pennsylvania Worker and Community Right-to-Know Law

2-Propanol (CAS 67-63-0)

Amorphous silica (CAS 61790-53-2)

Distillates (petroleum), hydrotreated light (CAS 64742-47-8)

Oleic acid (CAS 112-80-1)

Stoddard Solvent (CAS 8052-41-3)

US. Rhode Island RTK

2-Propanol (CAS 67-63-0)

Distillates (petroleum), hydrotreated light (CAS 64742-47-8)

Naphtha (petroleum), hydrodesulphurised heavy (CAS 64742-82-1)

Oleic acid (CAS 112-80-1)

Stoddard Solvent (CAS 8052-41-3)

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 2016 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

2-Propanol (CAS 67-63-0)

Cyclopentasiloxane (CAS 541-02-6)

Distillates (petroleum), hydrotreated light (CAS 64742-47-8)

Naphtha (petroleum), hydrodesulphurised heavy (CAS 64742-82-1)

Stoddard Solvent (CAS 8052-41-3)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

Toxic Substances Control Act (TSCA) Inventory

16. Other information, including date of preparation or last revision

Issue date 03-February-2017
Revision date 02-August-2018

Version # 02

United States & Puerto Rico

Further information The classification for health and environmental hazards is derived by a combination of calculation

methods and test data, if available.

NFPA ratings



List of abbreviations LC50: Lethal Concentration, 50%.

LD50: Lethal Dose, 50%.

PEL: Permissible Exposure Limit. TWA: Time weighted average. STEL: Short term exposure limit.

References ACGIH

EPA: Acquire database

NLM: Hazardous Substances Data Base

US. IARC Monographs on Occupational Exposures to Chemical Agents

PW-C, AG-716, AG916 SDS US

936244 Version #: 02 Revision date: 02-August-2018 Issue date: 03-February-2017

Yes

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Disclaimer

Granitize Products Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.