

Versio 3.0	'n	Revision Date: 10/22/2019		DS Number: 00000001108	Date of last issue: 10/15/2019 Date of first issue: 08/14/2017
SECTION 1. IDENTIFICATION					
Р	roduc	t name	:	CYCLO BPC NO	N-CHLOR 10% VOC 5 GA
Р	roduc	t code	:	C119CA10VOC	
	Manufacturer or supplier's of Company name of supplier				LC
А	Address		:	Dallas TX 75225	
E	Email Address		:	EHS@niteoprodu	cts.com
Т	Telephone		:	1-844-696-4836	
	Emergency telephone num- ber		:	1-800-424-9300 /	1-703-741-5970
R	ecom	mended use of the c	hen	nical and restriction	ons on use
R	Recommended use		:	BRAKE PARTS C	CLEANER
R	Restrictions on use		:	Use only outdoors	s or in a well-ventilated area.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Flammable liquids	:	Category 2
Skin irritation	:	Category 2
Eye irritation	:	Category 2A
Reproductive toxicity	:	Category 2
Specific target organ toxicity - single exposure	:	Category 3 (Central nervous system)
Specific target organ toxicity - repeated exposure (Inhala- tion)	:	Category 2 (Neurologic: other (neuropsychological effects, audi- tory dysfunction and effects on color vision))
Aspiration hazard	:	Category 1

GHS label elements



Version 3.0	Revision Date: 10/22/2019	SDS Number: 600000001108	Date of last issue: 10/15/2019 Date of first issue: 08/14/2017
Haza	rd pictograms		
Signa	al word	: Danger	
Haza	rd statements	May be fatal if Causes skin irr Causes serious May cause dro Suspected of d May cause dar logical effects,	
Preca	autionary statements	Prevention:	
		Do not handle understood. Keep away from smoking. Keep containen Ground/bond c Use explosion- Use only non-s Take precautio Do not breathe Wash skin thor Use only outdo	ontainer and receiving equipment. proof electrical/ ventilating/ lighting equipment.
		IF ON SKIN (or clothing. Rinse IF INHALED: R for breathing. O IF IN EYES: Ri Remove contac rinsing. IF exposed or o Do NOT induce If skin irritation If eye irritation Take off contar	occurs: Ğet medical advice/ attention. persists: Get medical advice/ attention. minated clothing and wash before reuse. Use dry sand, dry chemical or alcohol-resistant
		Storage: Store in a well-	ventilated place. Keep container tightly closed.
			ventilated place. Keep cool.



Version 3.0	Revision Date: 10/22/2019	SDS Number: 600000001108	Date of last issue: 10/15/2019 Date of first issue: 08/14/2017
		Store locked up).
Disposal:			
Dispose of contents/ container to an approved waste dispo			tents/ container to an approved waste disposal

plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

CAS-No.	Concentration (% w/w)
67-64-1	>= 90 - < 100
108-88-3	>= 5 - < 10
426260-76-6	>= 1 - < 5
	67-64-1 108-88-3

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4. FIRST AID MEASURES

General advice	•	Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later. Do not leave the victim unattended.
If inhaled	:	Move to fresh air. Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	:	If on clothes, remove clothes. Remove contaminated clothing. If irritation develops, get med- ical attention. If on skin, rinse well with water. Wash contaminated clothing before re-use. If skin irritation persists, call a physician.
In case of eye contact	:	Immediately flush eye(s) with plenty of water. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	:	Obtain medical attention. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.



Version	Revision Date: 10/22/2019	SDS Number:	Date of last issue: 10/15/2019
3.0		600000001108	Date of first issue: 08/14/2017
	important symptoms effects, both acute and red	and ketosis follo May be fatal if s Causes skin irrit Causes serious May cause drow Suspected of da	eye irritation. vsiness or dizziness. maging the unborn child. age to organs through prolonged or repeated

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Water spray Carbon dioxide (CO2) Dry chemical Alcohol-resistant foam
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during fire- fighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion prod- ucts	:	Carbon oxides
Specific extinguishing meth- ods	:	Product is compatible with standard fire-fighting agents.
Further information	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Use a water spray to cool fully closed containers.
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- : tive equipment and emer- gency procedures	Use personal protective equipment. Remove all sources of ignition. Ensure adequate ventilation. Avoid breathing dust. Beware of vapours accumulating to form explosive concentra- tions. Vapours can accumulate in low areas. Evacuate personnel to safe areas. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
Environmental precautions :	Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system.



Version 3.0	Revision Date: 10/22/2019		0S Number: 0000001108	Date of last issue: 10/15/2019 Date of first issue: 08/14/2017
			If the product con respective author	taminates rivers and lakes or drains inform ities.
	nods and materials for ainment and cleaning up	:	sorbent material, miculite) and place	and then collect with non-combustible ab- (e.g. sand, earth, diatomaceous earth, ver- e in container for disposal according to local ons (see section 13).
SECTION	N 7. HANDLING AND ST	OR	AGE	
	ce on protection against and explosion	:	(which might caus Electrically bond a equipment before tions may be nece conductive contai during product tra tion Association of Keep away from o ignition. Use only explosio	action to avoid static electricity discharge se ignition of organic vapours). and ground all containers, personnel and transfer or use of material. Special precau- essary to dissipate static electricity for non- ners. Use proper bonding and grounding nsfer as described in National Fire Protec- locument NFPA 77. open flames, hot surfaces and sources of n-proof equipment. naked flame or any incandescent material.
Advi	ce on safe handling	:	Avoid formation of Provide sufficient Do not breathe va Do not smoke. Take precautiona Avoid contact with Dispose of rinse v regulations. Container hazard Smoking, eating a plication area.	air exchange and/or exhaust in work rooms. apours/dust. ry measures against static discharges. n skin and eyes. vater in accordance with local and national
Cond	ditions for safe storage	:	place.	
	ner information on stor- stability	:	No decomposition	n if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of	Control parame- ters / Permissible	Basis	
------------	---------	------------------------	---------------------------------------	-------	--



Ver 3.0	sion	Revision Da 10/22/2019
	Acetor	ne

n Date:

SDS Number: 600000001108

Date of last issue: 10/15/2019 Date of first issue: 08/14/2017

		exposure)	concentration	
Acetone	67-64-1	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	250 ppm	NIOSH REL
			590 mg/m3	
		TWA	1,000 ppm 2,400 mg/m3	OSHA Z-1
		TWA	750 ppm 1,800 mg/m3	OSHA P0
		STEL	1,000 ppm 2,400 mg/m3	OSHA P0
Toluene	108-88-3	TWA	20 ppm	ACGIH
		TWA	100 ppm 375 mg/m3	NIOSH REL
		ST	150 ppm 560 mg/m3	NIOSH REL
		TWA	200 ppm	OSHA Z-2
		CEIL	300 ppm	OSHA Z-2
		Peak	500 ppm (10 minutes)	OSHA Z-2
		TWA	100 ppm 375 mg/m3	OSHA P0
		STEL	150 ppm 560 mg/m3	OSHA P0
Heptane, branched, cyclic and linear	426260-76-6	TWA	400 ppm	ACGIH
		STEL	500 ppm	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam- pling time	Permissible concentra- tion	Basis
Acetone	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI
Toluene	108-88-3	Toluene	In blood	Prior to last shift of work- week	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
		o-Cresol	Urine	End of shift (As soon as possible	0.3 mg/g Creatinine	ACGIH BEI



Vers 3.0	sion	Revision Date: 10/22/2019		OS Number: 0000001108	Date of last issue: 1 Date of first issue: 0	
					after exposu ceases	
	Engin	eering measures	:	ventilation to main	ntain exposure below ow levels that cause	and/or local exhaust) exposure guidelines (if known, suspected or
	Perso	nal protective equi	ipment			
	Respir	atory protection	:	In the case of vap proved filter.	oour formation use a	respirator with an ap-
	Hand p	protection				
	Rei	marks	:	er). The suitability cussed with the p	for a specific workpl	ctive gloves. Discard
	Eye pr	otection	:		blash goggles when t yes to liquid, vapor o	here is the potential for r mist.
	Skin a	nd body protection	:		ng	
	Hygier	ne measures	:	Handle in accorda practice. When using do no When using do no	ot smoke.	trial hygiene and safety

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Colour	:	clear
Odour	:	hydrocarbon-like
Odour Threshold	:	No data available
рН	:	No data available
Melting point/range	:	-78.88 °C
Boiling point/boiling range	:	56.11 °C
Flash point	:	-20 °C Method: closed cup



Vers 3.0	sion	Revision Date: 10/22/2019		S Number: 0000001108	Date of last issue: 10/15/2019 Date of first issue: 08/14/2017
	Evapor	ration rate	:	No data available	
	Self-ig	Inition	:	No data available	9
	Upper explosion limit / Upper flammability limit		:	7.1 %(V)	
		explosion limit / Lower ability limit	:	1.2 %(V)	
	Vapou	r pressure	:	No data available	
	Relativ	e vapour density	:	No data available	
	Density	/	:	6.62 lb/gal	
	Solubil Wat	ity(ies) ter solubility	:	partly soluble	
	Partitio octano	n coefficient: n- I/water	:	No data available	
	Viscosi Visc	ity cosity, dynamic	:	No data available	9
	Viso	cosity, kinematic	:	No data available	
	Molecu	ılar weight	:	No data available	9
	VOC %	6 By Weight	:	9 %	

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reac- tions	:	No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	:	Heat, flames and sparks.
Hazardous decomposition products	:	Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure Inhalation Eye contact Skin contact Ingestion



ersion .0	Revision Date: 10/22/2019		DS Number: 00000001108	Date of last issue: 10/15/2019 Date of first issue: 08/14/2017
Acute	e toxicity			
Not c	lassified based on ava	ilable	information.	
Produ	uct:			
Acute	inhalation toxicity	:	Acute toxicity e Exposure time Test atmosphe Method: Calcu	ere: vapour
Com	ponents:			
Aceto	one:			
Acute	e oral toxicity	:	LD50 (Rat, fen	nale): 5,800 mg/kg
Acute	inhalation toxicity	:	LC50 (Rat, fen Exposure time Test atmosphe	: 4 h
Acute	e dermal toxicity	:	LD50 (Rabbit):	> 7,426 mg/kg
Tolue	ene:			
Acute	e oral toxicity	:	LD50 (Rat): >	5,000 mg/kg
Acute	inhalation toxicity	:	LC50 (Rat, ma Exposure time Test atmosphe	: 4 ĥ
Acute	e dermal toxicity	:	LD50 (Rabbit):	12,124 mg/kg
	corrosion/irritation es skin irritation.			
Prod				
Rema	arks: May cause skin ii	rritatio	n and/or dermat	iitis.
Com	ponents:			
Aceto Resul	one: It: Possibly irritating to	skin		
Resu	It: Repeated exposure	may	cause skin dryne	ess or cracking.
Tolue Resul	ene: It: Irritating to skin.			
	ane, branched, cyclic It: Irritating to skin.	and	linear:	
	ous eye damage/eye i	rritati	on	



Version	Revision Date:	SDS Number:
3.0	10/22/2019	60000001108

Date of last issue: 10/15/2019 Date of first issue: 08/14/2017

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:

Acetone:

Result: Irritating to eyes. Assessment: Irritating to eyes.

Toluene:

Result: Irritating to eyes.

Heptane, branched, cyclic and linear:

Result: Possibly irritating to eyes

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Heptane, branched, cyclic and linear:

Result: Substance is not considered to be potential skin sensitiser.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Suspected of damaging the unborn child.

Components:

Toluene:

Reproductive toxicity - As- : Some evidence of adverse effects on development, based on animal experiments.



 Version
 Revision Date:
 SDS Number:

 3.0
 10/22/2019
 600000001108

Date of last issue: 10/15/2019 Date of first issue: 08/14/2017

STOT - single exposure

May cause drowsiness or dizziness.

Components:

Acetone:

Exposure routes: Inhalation Target Organs: Nervous system Assessment: May cause drowsiness or dizziness.

Toluene:

Exposure routes: Inhalation Target Organs: Central nervous system Assessment: May cause drowsiness or dizziness.

Heptane, branched, cyclic and linear:

Exposure routes: Inhalation Target Organs: Central nervous system Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

May cause damage to organs (Neurologic: other (neuropsychological effects, auditory dysfunction and effects on color vision)) through prolonged or repeated exposure if inhaled.

Components:

Toluene:

Exposure routes: Inhalation Target Organs: Neurologic: other (neuropsychological effects, auditory dysfunction and effects on color vision) Assessment: May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Components:

Acetone:

May be harmful if swallowed and enters airways.

Toluene:

May be fatal if swallowed and enters airways.

Heptane, branched, cyclic and linear:

May be fatal if swallowed and enters airways.



Version	Revision Date:	SDS Number:	Date of last
3.0	10/22/2019	60000001108	Date of first

Date of last issue: 10/15/2019 Date of first issue: 08/14/2017

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

SECTION 12. ECOLOGICAL INFORMATION

Toxicity	
Additional ecological	: An environmental hazard cannot be excluded in the event of
information	unprofessional handling or disposal.
	Toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal	methods
----------	---------

Waste from residues	:	Dispose of in accordance with all applicable local, state and federal regulations.
Contaminated packaging	:	Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

International Regulations

IATA-DGR		
UN/ID No.	: UN 1993	
Proper shipping name	: Flammable liquid, n.o.s. (ACETONE, TOLUENE, Heptane))
Class	: 3	
Packing group	: 11	
Labels	: 3	
Packing instruction (cargo aircraft)	: 364	
Packing instruction (passenger aircraft)	: 353	
IMDG-Code		
UN number	: UN 1993	
Proper shipping name	: FLAMMABLE LIQUID, N.O.S. (ACETONE, TOLUENE, Heptane)	
Class	: 3	
Packing group	: 11	
Labels	: 3	



Version 3.0	Revision Date: 10/22/2019		DS Number: 00000001108	Date of last issue: 10/15/2019 Date of first issue: 08/14/2017			
	Code ne pollutant	:	F-E, <u>S-E</u> yes				
	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable for product as supplied.						
Natio	onal Regulations						
	FR D/NA number er shipping name	:	UN 1993 Flammable liquid (ACETONE, TOI	s, n.o.s. LUENE, Heptane)			
Labe ERG	ing group		3 II 3 128 no	- , -, -, -, -, -, -, -, -, -, -, -, -,			

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
Acetone	67-64-1	100	100 (F003)
Ethylbenzene	100-41-4	100	100 (F003)
Xylene	1330-20-7	100	100 (F003)
Toluene	108-88-3	100	100 (F005)
Benzene	71-43-2	10	10 (D018)
Acetone	67-64-1	5000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards	:	 Flammable (gases, aerosols, liquids, or se Serious eye damage or eye irritation Reproductive toxicity Specific target organ toxicity (single or rep Aspiration hazard Skin corrosion or irritation 		
SARA 313	:	: The following components are subject to reporting l tablished by SARA Title III, Section 313:		orting levels es-
		Toluene	108-88-3	>= 5 - < 10 %



Version	Revision Date:	SDS Number:	Date
3.0	10/22/2019	60000001108	Date

Date of last issue: 10/15/2019 Date of first issue: 08/14/2017

California Prop. 65

WARNING: This product can expose you to chemicals including Benzene, Ethylbenzene, which is/are known to the State of California to cause cancer, and Toluene, Benzene, n-Hexane, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16. OTHER INFORMATION

Further information



Revision Date : 10/22/2019

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN