



SAFETY DATA SHEET

Issue Date 03-27-2015

Revision Date 03-27-2015

Version 1

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name BRAKE & PARTS CLEANER

Other means of identification

Common Name: 1038
UN/ID No UN1950
Synonyms None
Product Type Aerosol Automotive Cleaner

Recommended use of the chemical and restrictions on use

Sale and Use Restrictions (NOT FOR SALE OR USE IN CALIFORNIA OR OTC STATES)
(FOR FURTHER INFORMATION REFER TO WWW.OTCAIR.ORG)
Recommended Use Restricted to professional users.
Uses advised against Consumer use

Details of the supplier of the safety data sheet

Supplier Address
MOC PRODUCTS CO., INC.
12306 Montague Street
Pacoima, CA 91331

Emergency telephone number

Company Phone Number MOC PRODUCTS CO., INC. (818) 794-3500
Emergency Telephone CHEMTREC 1-800-424-9300

2. HAZARDS IDENTIFICATION

Classification

Acute toxicity - Oral	Category 4
Acute toxicity - Dermal	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Reproductive toxicity	Category 2 Effects on or via lactation
Specific target organ toxicity (single exposure)	Category 1
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable Aerosols	Category 1

Label elements

Emergency Overview

Danger

Hazard statements

Toxic if swallowed
 Toxic in contact with skin
 Toxic if inhaled
 Causes skin irritation
 Suspected of damaging fertility or the unborn child
 May cause harm to breast-fed children
 Causes damage to organs
 May cause damage to organs through prolonged or repeated exposure
 May be fatal if swallowed and enters airways
 Extremely flammable aerosol
 Pressurized container: May burst if heated



Appearance Organic solvent based solution, Compressed gas

Physical state Aerosol

Odor Aromatic Solvent

Precautionary Statements - Prevention

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Wear protective gloves/protective clothing/eye protection/face protection
 Do not breathe dust/fume/gas/mist/vapors/spray
 Avoid contact during pregnancy/while nursing
 Wash face, hands and any exposed skin thoroughly after handling
 Do not eat, drink or smoke when using this product
 Use only outdoors or in a well-ventilated area
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking
 Pressurized container: Do not pierce or burn, even after use
 Do not spray on an open flame or other ignition source

Precautionary Statements - Response

Specific measures (see prevention statements and warnings on this label)
 Specific treatment (see response statements below and Section 4 of the Safety Data Sheet)
 If exposed: Call a POISON CONTROL CENTER or doctor/physician
 IF exposed
 Immediately call a POISON CONTROL CENTER or doctor/physician

IF ON SKIN: Wash with plenty of soap and water
 Call a POISON CONTROL CENTER or doctor/physician if you feel unwell
 If skin irritation occurs: Get medical advice/attention
 Take off contaminated clothing and wash before reuse
 IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing
 Call a POISON CONTROL CENTER or doctor/physician if you feel unwell
 Rinse mouth
 IF SWALLOWED: Immediately call a POISON CONTROL CENTER or doctor/physician
 Do not induce vomiting

Precautionary Statements - Storage

Store locked up
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F
 Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)**Other information**

- Very toxic to aquatic life with long lasting effects
 - Very toxic to aquatic life
 - DANGER! Poison. Vapor harmful. May be fatal or cause blindness if swallowed. Cannot be made non-poisonous. If swallowed, may be aspirated and cause lung damage, call physician immediately. May affect liver, kidneys, blood, or central nervous system. Causes irritation to skin, eyes and respiratory tract. Avoid eye contact.
- 65% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS Number	Weight %	Trade Secret
Heptane, Branched Cyclic	426260-76-6	0-60	*
Toluene	108-88-3	10-50	*
Isohexane	107-83-5	0-90	*
Heptane	142-82-5	0-30	*
Methyl Alcohol	67-56-1	10-30	*
Carbon Dioxide	124-38-9	5-10	*

* The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First aid measures**General advice**

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Immediately call a POISON CONTROL CENTER or doctor/physician.

Skin contact:

In case of skin contact, flush with plenty of soap and water for at least 15 minutes. Get medical attention. Remove contaminated clothing and shoes and launder before reuse.

Inhalation:

Move to fresh air in case of accidental inhalation of vapors. If not breathing, give artificial respiration. Consult a physician.

Eye contact:

Flush immediately with large amount of water for at least 15 minutes. Consult a physician.

Ingestion:

DO NOT INDUCE VOMITING. If swallowed, rinse mouth with water (only if the person is conscious). Call a physician or Poison Control Center immediately.

Notes to physician:

This product contains Methanol. Methanol can cause intoxication and central nervous system depression and metabolizes to formic acid and formaldehyde (metabolic acidosis), visual disturbances and blindness. Since metabolism is required for these toxic symptoms, their onset may be delayed from 6 to 30 hours following ingestion. Ethanol competes for the same metabolic pathway and has been used to prevent methanol metabolism. Ethanol administration is indicated in symptomatic patients or at blood methanol concentrations \geq 20 micrograms/dl. Methanol is effectively removed by hemodialysis.

Most important symptoms and effects, both acute and delayed**Symptoms**

Headache, Dizziness, Drowsiness, Shortness of breath (delayed symptom) and choking; Metabolic acidosis, Coma, Seizures, Unconsciousness, Blindness. Symptoms may be delayed.

Indication of any immediate medical attention and special treatment needed

Protection of first-aiders: Avoid breathing vapors. Avoid skin contact with product.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:

Use dry chemical, CO₂, water spray (fog) or alcohol resistant foam; Sand.

Small Fire Dry chemical or CO₂.

Large Fire Alcohol resistant foam, Water spray or fog. Sand.

Explosive properties: Pressurized container: May burst if heated. Risk of explosion if heated under confinement. Vapors may form explosive mixtures with air.

Specific hazards arising from the chemical

Extremely flammable. Contents under pressure. Keep away from ignition sources and open flames. Exposure of containers to extreme heat and flames can cause them to rupture, often with violent force. Vapors are heavier than air and may travel along surfaces to remote ignition sources and flash back. Flash back possible over considerable distance. Keep product and empty container away from heat and sources of ignition. VAPOR MAY CAUSE FLASH FIRE. Will be easily ignited by heat, sparks or flames. Vapors may travel to areas away from work site before igniting/flashing back to vapor source. Sealed containers may rupture when heated. Thermal decomposition can lead to release of irritating and toxic gases and vapors.

Hazardous combustion products Carbon monoxide, Carbon dioxide (CO₂), Hydrocarbons, Aldehydes, Formic acid, Formaldehyde. Note: Formaldehyde is a skin and respiratory sensitizer, eye and throat irritant, acute toxicant, and potential cancer hazard.

Specific methods:

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge Yes. May be ignited by heat, sparks or flames.

Special firefighting procedures:

Wear approved positive pressure self contained breathing apparatus (SCBA) and protective clothing. Use water spray or fog to cool cans.

Component	ACGIH - test
Toluene	0.02
108-88-3 (10-50)	0.03
	0.3
Methyl Alcohol	15
67-56-1 (10-30)	

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions: Remove all sources of ignition. Ventilate closed spaces before entry. Pay attention to flashback. Use spark-proof tools and explosion-proof equipment. Use personal protective equipment. For personal protective equipment see Section 8. Avoid contact with skin, eyes and clothing.

For emergency responders Use personal protection recommended in Section 8. Ventilate the area. Remove all sources of ignition. Be aware that gases can spread at ground level (heavier than air) and pay attention to the wind direction. Pay attention to flashback.

Environmental precautions

Environmental precautions: Environmental hazard: Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. Water runoff can cause environmental damage. Avoid subsoil penetration.

Methods and material for containment and cleaning up

Methods for containment Remove all sources of ignition. Ventilate area. Prevent further leakage or spillage if safe to do so. Use non-sparking tools. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container.

Methods for cleaning up: Pressurized container: Do not pierce or burn, even after use. Clean-up methods - small spillage: Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a chemical waste container for later disposal. Large spills present a vapor explosion and liquid fire hazard; evacuate area and ensure response by personnel trained and equipped to respond to flammable material incident or off-site emergency responders or fire department.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling: Contents under pressure. Do not puncture, incinerate or store above 120°F. Exposure to high temperature may cause bursting. Protect from direct sunlight. Protect against physical damage. Store between 40 and 120 °F. Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Avoid all possible sources of ignition (spark or flame). Store away from incompatible materials (See section 7 or 10 of the SDS). Store in a cool, well ventilated area. Do not store in the passenger compartment of an automobile. Pregnant or breastfeeding women must not handle this product.

Conditions for safe storage, including any incompatibilities

Technical measures/precautions: Ventilation - Local (Mechanical if used indoors on a continuous basis). Eye wash and safety shower should be easily accessible.

Materials to avoid: Oxidizing agents, Acid anhydrides, Acid chlorides, Alkali metals, Reducing agents, Acids.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Components	ACGIH TLV	OSHA Exposure Limits:	NIOSH IDLH
Heptane, Branched Cyclic 426260-76-6	TWA: 400 ppm	TWA: 500 ppm	-
Toluene 108-88-3	TWA: 20 ppm	TWA: 200 ppm TWA: 100 ppm TWA: 375 mg/m ³	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³
Isohexane 107-83-5	STEL: 1000 ppm TWA: 500 ppm	TWA: 500 ppm TWA: 1800 mg/m ³	TWA: 100 ppm TWA: 350 mg/m ³ Ceiling: 510 ppm 15 min Ceiling: 1800 mg/m ³ 15 min

Heptane 142-82-5	STEL: 500 ppm TWA: 400 ppm	TWA: 500 ppm TWA: 2000 mg/m ³ TWA: 400 ppm TWA: 1600 mg/m ³	IDLH: 750 ppm TWA: 85 ppm TWA: 350 mg/m ³ Ceiling: 440 ppm 15 min Ceiling: 1800 mg/m ³ 15 min
Methyl Alcohol 67-56-1	S* STEL: 250 ppm TWA: 200 ppm	TWA: 200 ppm TWA: 260 mg/m ³	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m ³ STEL: 250 ppm STEL: 325 mg/m ³
Carbon Dioxide 124-38-9	STEL: 30000 ppm TWA: 5000 ppm	TWA: 5000 ppm TWA: 9000 mg/m ³ TWA: 10000 ppm TWA: 18000 mg/m ³	IDLH: 40000 ppm TWA: 5000 ppm TWA: 9000 mg/m ³ STEL: 30000 ppm STEL: 54000 mg/m ³

Appropriate engineering controls

Engineering measures: Ventilation - Local (Mechanical if used indoors on a continuous basis). Eye wash and safety shower should be easily accessible.

Individual protection measures, such as personal protective equipment

- Eye/face protection** Wear safety glasses with side shields (or goggles). If splashes are likely to occur, wear: Face protection shield.
- Skin and body protection** Wear normal work clothing including long pants, long-sleeved shirts and foot covering to prevent direct contact of the product with the skin. Launder clothing before reuse. If skin irritation develops, contact your facility health and safety professional or your local safety equipment supplier to determine the proper personal protective equipment for your use. Wear chemical resistant gloves (consult your safety equipment supplier). Additional body garments such as chemically resistant suit, boots and face shield should be used based upon task being performed.
- Respiratory protection** Respiratory protection is not required under normal conditions of use. If workplace exposure limit(s) of product or any component is exceeded, a NIOSH-approved air purifying respirator used in accordance with the OSHA Respiratory Protection Standard [29 CFR 1910.134] is recommended in the absence of adequate ventilation during normal use (see your industrial hygienist). Emergency response/release cleanup may require additional respiratory protection, including SCBAs. Administrative or engineering controls should be implemented to reduce exposure.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. When using do not eat, drink or smoke. Use personal protective equipment as required. Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mists. Wash face, hands and any exposed skin thoroughly after handling. Take off all contaminated clothing and wash it before reuse. Wash contaminated clothing before reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Aerosol	Odor	Aromatic Solvent
Appearance	Organic solvent based solution, Compressed gas	Odor threshold	No information is available
Color	Clear, Colorless		
Property	Values	Remarks: • Method	
pH	N/A	Not applicable	
Melting point/freezing point	>= -79 °C / -110 °F		
Boiling point/boiling range	88 °C / 190 °F	(Based on lowest liquid component)	

Flash point	-9.0 °C / 16 °F	(Based on lowest liquid component)
Evaporation rate	Slower than ether	
Flammability (solid, gas)	No information is available	
Flammability Limits in Air		
Upper flammability limits	No data available	
Lower flammability limit	No data available	
Vapor pressure	>655 kPa	Ambient temperature (kPa)
Vapor density	>1 (air = 1)	Heavier than air
Specific Gravity	0.79	
Water solubility	Negligible	
Solubility in other solvents	No data available	
Partition coefficient	No data available	
Autoignition temperature	223 °C / 433 °F	(Lowest component)
Decomposition temperature	No data available	
Kinematic viscosity	0.83 mm ² /s	@ 38 °C
Dynamic viscosity	No data available	
Explosive properties	No data available	
Oxidizing properties	No data available	

Other information

Softening point	No data available
Molecular weight	No data available
VOC Content (%)	94.0
Density	0.79 g/cc
Bulk density	No data available

10. STABILITY AND REACTIVITY**Reactivity**

Reactivity Stable under normal conditions. Avoid direct exposure to sunlight.

Chemical stability

Stability Avoid open flames and temperatures above 120°F or direct sunlight.

Possibility of Hazardous Reactions

Reacts with oxidizing agents. Vapors may form explosive mixture with air.

Hazardous polymerization Hazardous polymerization does not occur.

Conditions to avoid

Temperatures above 120 °F. Heat, flames and sparks. Keep away from direct sunlight.

Incompatible materials

Materials to avoid: Oxidizing agents, Acid anhydrides, Acid chlorides, Alkali metals, Reducing agents, Acids.

Hazardous Decomposition Products

Hazardous Decomposition Products Carbon monoxide, Carbon dioxide (CO₂), Hydrocarbons, Aldehydes, Formic acid, Formaldehyde. Note: Formaldehyde is a skin and respiratory sensitizer, eye and throat irritant, acute toxicant, and potential cancer hazard.

11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Product information	Toxic by inhalation, in contact with skin and if swallowed. DANGER! Poison. Vapor harmful. May be fatal or cause blindness if swallowed. Cannot be made non-poisonous. If swallowed, may be aspirated and cause lung damage, call physician immediately. May affect liver, kidneys, blood, or central nervous system. Causes irritation to skin, eyes and respiratory tract. Avoid eye contact.
Inhalation	Toxic by inhalation. Avoid breathing vapors or mists. Propellant is a simple asphyxiant.
Eye contact	Inhalation, ingestion, or skin absorption of methanol can cause blindness.
Skin Contact	Toxic in contact with skin. May be absorbed through the skin in harmful amounts. Causes skin irritation. Avoid contact with skin and clothing.
Ingestion	Toxic if swallowed. MAY BE FATAL OR CAUSE BLINDNESS IF SWALLOWED.

Components	Oral LD50	Dermal LD50	Inhalation LC50
Heptane, Branched Cyclic 426260-76-6	> 5000 mg/kg (Rat) - Read across	> 2000 mg/kg (Rabbit)- Read across	= 103 mg/l (Rat) 4h ; 25000 ppm (Rat) 4h
Toluene 108-88-3	= 636 mg/kg (Rat)	= 8390 mg/kg (Rabbit)	= 12.5 mg/L (Rat) 4 h > 26700 ppm (Rat) 1 h
Isohexane 107-83-5	= 15000 mg/kg (Rat)	-	-
Heptane 142-82-5	> 5000 mg/kg (Rat) - Read across	= 3000 mg/kg (Rabbit)	= 103 g/m ³ (Rat) 4 h; 25000 ppm (Rat) 4h
Methyl Alcohol 67-56-1	= 5628 mg/kg (Rat)	-	= 83.2 mg/L (Rat) 4 h
Carbon Dioxide 124-38-9	-	-	-

Information on toxicological effects

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization	Not expected to cause skin sensitization. Not classified as a respiratory sensitizer.
Mutagenic effects:	No data available to indicate product or any components present at or greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	Category 3: Not classifiable as carcinogenic.

Components	IARC:
Toluene 108-88-3	Group 3 (not classified)

Reproductive toxicity	This product contains Toluene (CAS#108-88-3). Category 2: Substances which should be regarded as if they impair fertility in humans. May cause harm to breastfed babies.
Developmental Toxicity	Toluene (CAS#108-88-3): May cause harm to the unborn child.
STOT - single exposure	This product is classified as STOT single exposure Category 1. Causes damage or disorder to: Eyes, Kidney, Liver, Heart, Central nervous system. Causes dizziness or drowsiness.
STOT - repeated exposure	This product is classified as STOT repeated exposure Category 2. May cause disorder and damage to the: Reproductive System, Bladder, Brain.
Chronic toxicity	Experiments have shown reproductive toxicity effects on laboratory animals. May cause harm to the unborn child. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Repeated or prolonged exposure may cause central nervous system damage. Prolonged skin contact may defat the skin and produce dermatitis.
Target Organ Effects	Eyes, Ears, Heart, Liver; Kidney, Bladder, Brain, Central nervous system, Reproductive System.
Neurological effects	Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Repeated or prolonged overexposure to solvents may cause permanent damage to the nervous system.

Other adverse effects

Experiments have shown reproductive toxicity effects in male and female laboratory animals. Inhalation studies on toluene have demonstrated the development of inflammatory and ulcerous lesions of the penis, prepuce, and scrotum in animals. Auditory system: prolonged and repeated exposure to high concentrations have resulted in hearing losses in rats. Solvent abuse and noise interaction in the work environment may cause hearing loss. May be fatal if swallowed and enters airways.

Aspiration hazard

Numerical measures of toxicity - Product information

Unknown Acute Toxicity 65% of the mixture consists of ingredient(s) of unknown toxicity
The following values are calculated based on chapter 3.1 of the GHS document .
ATEmix (oral) 332 mg/kg
ATEmix (dermal) 1075 mg/kg
ATEmix (inhalation-dust/mist) 2.1 mg/l
ATEmix (inhalation-vapor) 26 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Aquatic Toxicity (Acute): Very toxic to aquatic life. Aquatic Toxicity (Chronic): Very toxic to aquatic life with long lasting effects.

Toluene 108-88-3	
Algae/aquatic plants	12.5: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 433: 96 h Pseudokirchneriella subcapitata mg/L EC50
Fish	11.0 - 15.0: 96 h Lepomis macrochirus mg/L LC50 static 14.1 - 17.16: 96 h Oncorhynchus mykiss mg/L LC50 static 15.22 - 19.05: 96 h Pimephales promelas mg/L LC50 flow-through 5.89 - 7.81: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 50.87 - 70.34: 96 h Poecilia reticulata mg/L LC50 static 12.6: 96 h Pimephales promelas mg/L LC50 static 28.2: 96 h Poecilia reticulata mg/L LC50 semi-static 5.8: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 54: 96 h Oryzias latipes mg/L LC50 static
Crustacea	5.46 - 9.83: 48 h Daphnia magna mg/L EC50 Static 11.5: 48 h Daphnia magna mg/L EC50
Heptane 142-82-5	
Fish	375.0: 96 h Cichlid fish mg/L LC50
Crustacea	10: 24 h Daphnia magna mg/L EC50
Methyl Alcohol 67-56-1	
Fish	13500 - 17600: 96 h Lepomis macrochirus mg/L LC50 flow-through 18 - 20: 96 h Oncorhynchus mykiss mg/L LC50 static 19500 - 20700: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 28200: 96 h Pimephales promelas mg/L LC50 flow-through 100: 96 h Pimephales promelas mg/L LC50 static

Persistence and degradability

No information is available.

Bioaccumulation

Bioaccumulative potential.

Mobility

No information is available.

Components	Partition coefficient
Toluene 108-88-3	2.73
Heptane 142-82-5	>3.00
Methyl Alcohol 67-56-1	-0.77

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Dispose of in accordance with federal, state and local regulations.

Contaminated packaging Pressurized container: Do not pierce or burn, even after use. Dispose of in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION

DOT

UN/ID No UN1950
Proper shipping name Aerosols
Hazard Class 2.1
Packing Group N/A
Emergency Response Guide Number 126

IATA

UN/ID No UN1950
Proper shipping name Aerosols, flammable
Hazard Class 2.1
Packing Group N/A

IMDG

UN/ID No UN1950
Proper shipping name Aerosols
Hazard Class 2
Packing Group N/A

Limited quantity (LQ) < 1 Liter

15. REGULATORY INFORMATION

International Inventories

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) - This product contains a chemical or chemicals which is/are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Components	CAS Number	Weight %	SARA 313 - Threshold Values %
Toluene	108-88-3	10-50	1.0 % de minimis concentration

Methyl Alcohol	67-56-1	10-30	1.0 % de minimis concentration
----------------	---------	-------	--------------------------------

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	Yes
Sudden release of pressure hazard	Yes
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Components	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Toluene 108-88-3	1000 lb 1 lb		RQ 1000 lb final RQ RQ 454 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ
Methyl Alcohol 67-56-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

State Regulations (RTK)

California Proposition 65

This product contains chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.

U.S. State Right-to-Know Regulations

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION

NFPA rating:

Health hazards 2

Flammability -

Instability 0

Physical and Chemical Properties NFPA Level 2 aerosol

HMIS health rating:

Health hazards 2*

Flammability 4

Physical hazards 1

Personal protection B, Flammability classification is under HMIS III

Prepared By Environmental Health and Safety Department

Issue Date 03-27-2015

Revision Date 03-27-2015

Revision Note

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet