Valvoline	Page: 1
SAFETY DATA SHEET	Revision Date: 06/07/2018
	Print Date: 8/23/2018
	SDS Number: R0200299
NAPA® PREM PERF Automatic Transmission Fluid	Version: 1.5
NP75200	

29 CFR 1910.1200 (OSHA HazCom 2012)

# **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

**Product identifier** 

Trade name : NAPA® PREM PERF

Automatic Transmission Fluid

Details of the supplier of the safety data	Emergency telephone number
sheet	1-800-VALVOLINE (1-800-825-8654)
Valvoline LLC	, , , , , , , , , , , , , , , , , , ,
100 Valvoline Way	Regulatory Information Number
Lexington, KY 40509	1-800-TEAMVAL (1-800-832-6825)
United States of America (USA)	,
1-800-TEAMVAL (1-800-832-6825)	Product Information
,	1-800-TEAMVAL (1-800-832-6825)

# **SECTION 2. HAZARDS IDENTIFICATION**

## **GHS Classification**

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

## **GHS** label elements

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

# Other hazards

None known.

## **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Hazardous components** 

nazaradad dempending			
Chemical name	CAS-No.	Classification	Concentration (%)
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC		This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).	>=90.00 - <= 100.00
I and the second			ſ

Valvoline	Page: 2
SAFETY DATA SHEET	Revision Date: 06/07/2018
	Print Date: 8/23/2018
	SDS Number: R0200299
NAPA® PREM PERF Automatic Transmission Fluid	Version: 1.5
NP75200	

HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	Asp. Tox. 1; H304	>=10.00 - < 15.00
MINERAL OIL		This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).	>=1.50 - < 5.00
METHACRYLATE COPOLYMER		Eye Irrit. 2A; H319	>=1.50 - < 5.00

#### **SECTION 4. FIRST AID MEASURES**

General advice : No hazards which require special first aid measures.

If inhaled : If breathed in, move person into fresh air.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : First aid is not normally required. However, it is

recommended that exposed areas be cleaned by washing

with soap and water.

In case of eye contact : Remove contact lenses.

Protect unharmed eye.

If swallowed : Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

: Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary

abnormalities.

Signs and symptoms of exposure to this material through

Valvoline	Page: 3
SAFETY DATA SHEET	Revision Date: 06/07/2018
	Print Date: 8/23/2018
	SDS Number: R0200299
NAPA® PREM PERF Automatic Transmission Fluid	Version: 1.5
NP75200	

breathing, swallowing, and/or passage of the material through

the skin may include:

acne

stomach or intestinal upset (nausea, vomiting, diarrhea)

irritation (nose, throat, airways)

Notes to physician : No hazards which require special first aid measures.

## **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water spray Foam

Carbon dioxide (CO2)

Dry chemical

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: carbon dioxide and carbon monoxide

Hydrocarbons

Specific extinguishing

methods

:

Product is compatible with standard fire-fighting agents.

Further information : Standard procedure for chemical fires.

Special protective equipment

for firefighters

: In the event of fire, wear self-contained breathing apparatus.

### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures

: Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

Valvoline.	Page: 4
SAFETY DATA SHEET	Revision Date: 06/07/2018
	Print Date: 8/23/2018
	SDS Number: R0200299
NAPA® PREM PERF Automatic Transmission Fluid	Version: 1.5
NP75200	

# **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Smoking, eating and drinking should be prohibited in the

application area.

For personal protection see section 8.

Materials to avoid : No materials to be especially mentioned.

# **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL
MINERAL OIL		TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0

Valvoline	Page: 5
SAFETY DATA SHEET	Revision Date: 06/07/2018
	Print Date: 8/23/2018
	SDS Number: R0200299
NAPA® PREM PERF Automatic Transmission Fluid	Version: 1.5
NP75200	

TWA	5 mg/m3 Mist	NIOSH REL
ST	10 mg/m3 Mist	NIOSH REL
PEL	5 mg/m3 particulate	CAL PEL

**Engineering measures** : General room ventilation should be adequate for normal

conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known,

suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally

required.

Eye protection : Not required under normal conditions of use. Wear splash-

proof safety goggles if material could be misted or splashed

into eyes.

Skin and body protection : Wear as appropriate:

Safety shoes

Wear resistant gloves (consult your safety equipment

supplier).

Hygiene measures : General industrial hygiene practice.

## **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Physical state : liquid

Colour : red

Odour : hydrocarbon-like

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : No data available

Flash point : 394 - 480 °F / 201 - 249 °C

Method: Cleveland open cup

Evaporation rate : > 1

Valvoline	Page: 6
SAFETY DATA SHEET	Revision Date: 06/07/2018
	Print Date: 8/23/2018
	SDS Number: R0200299
NAPA® PREM PERF Automatic Transmission Fluid	Version: 1.5
NP75200	

Ethyl Ether

Flammability (solid, gas) : No data available

Upper explosion limit : 6 %(V)

GLP: Calculated Explosive Limit

Lower explosion limit : 1 %(V)

GLP: Calculated Explosive Limit

Vapour pressure : 0.0133333 hPa (21.11 °C)

Calculated Vapor Pressure

Relative vapour density : No data available

Relative density : No data available

Density : 0.862 g/cm3 (15.56 °C)

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : ca. 43 mm2/s (40 °C)

Oxidizing properties : No data available

# **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous

reactions

: Product will not undergo hazardous polymerization.

Conditions to avoid : excessive heat

Incompatible materials : Strong oxidizing agents

Valvoline.	Page: 7
SAFETY DATA SHEET	Revision Date: 06/07/2018
	Print Date: 8/23/2018
	SDS Number: R0200299
NAPA® PREM PERF Automatic Transmission Fluid	Version: 1.5
NP75200	

Hazardous decomposition

products carbon dioxide and carbon monoxide

Hydrocarbons

## **SECTION 11. TOXICOLOGICAL INFORMATION**

Information on likely routes of : Inhalation

exposure Skin contact

Eye Contact Ingestion

**Acute toxicity** 

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

Skin corrosion/irritation

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Result: Slight, transient irritation

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result: Slight, transient irritation

MINERAL OIL:

Result: Slight, transient irritation

METHACRYLATE COPOLYMER:

Result: No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

**Product:** 

Remarks: Unlikely to cause eye irritation or injury.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Result: No eye irritation

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result: Slight, transient irritation

MINERAL OIL:

Result: Slight, transient irritation

Valvoline	Page: 8
SAFETY DATA SHEET	Revision Date: 06/07/2018
	Print Date: 8/23/2018
	SDS Number: R0200299
NAPA® PREM PERF Automatic Transmission Fluid	Version: 1.5
NP75200	

#### METHACRYLATE COPOLYMER:

Result: Irritating to eyes.

# Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information. Respiratory sensitisation: Not classified based on available information.

**Product:** 

Assessment: Does not cause skin sensitisation.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

**Aspiration toxicity** 

Not classified based on available information.

**Product:** 

No aspiration toxicity classification

#### Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

No aspiration toxicity classification

#### HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

# **Further information**

**Product:** 

Remarks: No data available

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

#### **SECTION 12. ECOLOGICAL INFORMATION**

Valvoline	Page: 9
SAFETY DATA SHEET	Revision Date: 06/07/2018
	Print Date: 8/23/2018
	SDS Number: R0200299
NAPA® PREM PERF Automatic Transmission Fluid	Version: 1.5
NP75200	

**Ecotoxicity** 

**Product:** 

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

: Not classified based on available information. Chronic aquatic toxicity

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Toxicity to fish : LL50 (Fish): > 100 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EL50 (Aquatic invertebrates): > 10,000 mg/l

Exposure time: 48 h

Toxicity to algae : EL50 (Algae, algal mat (Algae)): > 100 mg/l

Exposure time: 72 h

Toxicity to fish (Chronic

toxicity)

: NOEC (Fish): 10 mg/l

aquatic invertebrates (Chronic toxicity)

Toxicity to daphnia and other : NOEC (Aquatic invertebrates): 10 mg/l

Persistence and degradability

Components: No data available

Bioaccumulative potential

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Partition coefficient: n-: log Pow: Expected > 7

octanol/water

No data available Mobility in soil Components:

No data available

Other adverse effects

No data available

**Product:** 

Additional ecological

: No data available

information

**Components:** 

**SECTION 13. DISPOSAL CONSIDERATIONS** 

**Disposal methods** 

Valvoline.	Page: 10
SAFETY DATA SHEET	Revision Date: 06/07/2018
	Print Date: 8/23/2018
	SDS Number: R0200299
NAPA® PREM PERF Automatic Transmission Fluid	Version: 1.5
NP75200	

General advice : Dispose of in accordance with all applicable local, state and

federal regulations.

Contaminated packaging : Empty remaining contents.

# **SECTION 14. TRANSPORT INFORMATION**

# International transport regulations

## **REGULATION**

ID NUMBER	PROPER SHIPPING NAME	*HAZARD	SUBSIDIARY	PACKING	MARINE
		CLASS	HAZARDS	GROUP	POLLUTANT /
					LTD. QTY.

# **U.S. DOT - ROAD**

Not dangerous goods	

# CFR\_RAIL\_C

Not dangerous goods	

## **U.S. DOT - INLAND WATERWAYS**

Not dangerous goods

# TDG\_ROAD\_C

Not dangerous goods	

# TDG\_RAIL\_C

Not dangerous goods	

# TDG\_INWT\_C

Not dangerous goods	

# INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods	

## **INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO**

Not dangerous goods	

# **INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER**

Not dangerous goods

Valvoline	Page: 11
SAFETY DATA SHEET	Revision Date: 06/07/2018
	Print Date: 8/23/2018
	SDS Number: R0200299
NAPA® PREM PERF Automatic Transmission Fluid	Version: 1.5
NP75200	

## MX\_DG

Not dangerous goods		

## \*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	no

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

#### **SECTION 15. REGULATORY INFORMATION**

# **EPCRA - Emergency Planning and Community Right-to-Know Act CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ. SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : No SARA Hazards

SARA 313 This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop 65 This product does not contain any chemicals known to State

of California to cause cancer, birth defects, or any other

reproductive harm.

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TSCA : On TSCA Inventory


## Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

Valvoline	Page: 12
SAFETY DATA SHEET	Revision Date: 06/07/2018
	Print Date: 8/23/2018
	SDS Number: R0200299
NAPA® PREM PERF Automatic Transmission Fluid	Version: 1.5
NP75200	

## **SECTION 16. OTHER INFORMATION**

Further information
Revision Date: 06/07/2018



NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

#### **Full text of H-Statements**

H304 May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation.

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet:

ACGIH: American Conference of Industrial Hygienists

BEI : Biological Exposure Index

Valvoline.	Page: 13
SAFETY DATA SHEET	Revision Date: 06/07/2018
	Print Date: 8/23/2018
	SDS Number: R0200299
NAPA® PREM PERF Automatic Transmission Fluid	Version: 1.5
NP75200	

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population. ICxx: Inhibitory Concentration for xx of a substance

Ecxx: Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD: Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment

STEL: Short-term exposure limit STOT: Specific Target Organ Toxicity

TLV: Threshold Limit Value TWA: Time-weighted average

vPvB: Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act

**DOT**: Department of Transportation

FIFRA: Federal Insecticide, Fungicide, and Rodenticide Act HMIRC: Hazardous Materials Information Review Commission

HMIS: Hazardous Materials Identification System NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety and Health Administration PMRA: Health Canada Pest Management Regulatory Agency

RTK : Right to Know

WHMIS: Workplace Hazardous Materials Information System