

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.05.2017 Page 1 of 10

Revision date: 09.14.2020

Security Coat

SECTION 1: Identification

Product identifier

Product name: Security Coat Product code: 738, 738G Additional information: Rev 4

Recommended use of the product and restriction on use

Relevant identified uses: Tire Repair Sealer

Uses advised against: Not determined or not applicable.

Reasons why uses advised against: Not determined or not applicable.

Manufacturer or supplier details

Manufacturer:
North America
Tech International
200 East Coshocton Street
Johnstown, OH 43031
1-740-967-9015
www.tech-international.com

Emergency telephone number:

United States
CHEMTREC

Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1-703-527-3887

SECTION 2: Hazard(s) identification

GHS classification: Not a hazardous substance or mixture

Label elements

Hazard pictograms: None

Signal word: None

Hazard statements: None

Precautionary statements: None

Hazards not otherwise classified: None

SECTION 3: Composition/information on ingredients

Identification	Name	Weight %
CAS number: 1333-86-4	Bounded Carbon Black	<5

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.05.2017 Page 2 of 10

Revision date: 09.14.2020

Security Coat

CAS number: 25322-68-3	Poly (ethylene oxide)	<1
CAS number: 67-56-1	Methanol	<0.1

Additional Information:

Carbon black is classified as a carcinogen only in its respirable form. Since the carbon black in this product is not respirable, the product itself is not classified as a carcinogen in the form presented.

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of the OSHA Hazard Communication Standard (29 CFR \$1910.1200).

SECTION 4: First aid measures

Description of first aid measures

General notes:

Show this Safety Data Sheet to the doctor in attendance

After inhalation:

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If symptoms develop or persist, seek medical advice/attention

After skin contact:

Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse. If symptoms develop or persist, seek medical advice/attention

After eye contact:

Rinse eyes with plenty of water for several minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention

After swallowing:

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention

Most important symptoms and effects, both acute and delayed

Acute symptoms and effects:

No significant acute effects

Delayed symptoms and effects:

No significant delayed effects

Immediate medical attention and special treatment

Specific treatment:

Not determined or not applicable.

Notes for the doctor:

Treat symptomatically

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.05.2017 Page 3 of 10

Revision date: 09.14.2020

Security Coat

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media:

Water mist/fog, carbon dioxide, dry chemical or alcohol resistant foam

Unsuitable extinguishing media:

Do not use water jet

Specific hazards during fire-fighting:

Thermal decomposition can lead to release of irritating gases and vapors

Special protective equipment for firefighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full-face piece operated in positive pressure mode

Special precautions:

Avoid contact with skin, eyes, hair and clothing. Do not breathe fumes/gas/mists/aerosols/vapors/dusts. Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers. Avoid unnecessary run-off of extinguishing media which may cause pollution

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Do not get on skin, eyes or on clothing. Avoid breathing mist. vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling. Remove contaminated clothing and launder before reuse

Environmental precautions:

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways. Discharge into the environment must be avoided

Methods and material for containment and cleaning up:

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Avoid breathing dust, mist, fumes, vapors or spray. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13)

Reference to other sections:

For personal protective equipment see Section 8. For disposal see Section 13

SECTION 7: Handling and storage

Precautions for safe handling:

Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Conditions for safe storage, including any incompatibilities:

Store in cool, dry, well-ventilated location out of direct sunlight. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Keep container tightly sealed. Store away from incompatible materials (See Section 10).

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.05.2017

Revision date: 09.14.2020

Security Coat

SECTION 8: Exposure controls/personal protection

Only those substances with limit values have been included below.

Occupational Exposure limit values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
WEEL	Poly (ethylene oxide)	25322-68-3	WEEL TWA 10.0 mg/m ³
United States (OSHA)	Bounded Carbon Black	1333-86-4	OSHA PEL TWA 3.5 mg/m ³
	Methanol	67-56-1	OSHA PEL TWA 200 ppm, 260 mg/m ³
NIOSH	Bounded Carbon Black	1333-86-4	NIOSH REL TWA 0.1 mg PAHs/m3 [Carbon black in presence of polycyclic aromatic hydrocarbons (PAHs)]
	Bounded Carbon Black	1333-86-4	NIOSH REL TWA 3.5 mg/m³ Ca
	Bounded Carbon Black	1333-86-4	IDLH: 1750 mg/m ³
	Methanol	67-56-1	NIOSH REL TWA 200 ppm [skin]
	Methanol	67-56-1	NIOSH REL TWA 260 mg/m³ [skin]
	Methanol	67-56-1	NIOSH REL ST 250 ppm [skin]
	Methanol	67-56-1	NIOSH REL ST 325 mg/m³ [skin]
ACGIH	Bounded Carbon Black	1333-86-4	TLV-TWA 3.0 mg/m ³
	Methanol	67-56-1	ACGIH TLV TWA: 200 ppm
	Methanol	67-56-1	ACGIH TLV STEL 250 ppm
United States (California)	Bounded Carbon Black	1333-86-4	8-hour TWA-PEL: 3.5 mg/m ³
	Methanol	67-56-1	8-hour PEL-TWA: 260 mg/m³ (200 ppm)
	Methanol	67-56-1	Ceiling limit: 1000 ppm
	Methanol	67-56-1	PEL-STEL: 325 mg/m³ (250 ppm)

Biological limit values:

No biological exposure limits noted for the ingredient(s).

Information on monitoring procedures:

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls.

Biological monitoring may also be appropriate for some substances.

Appropriate engineering controls:

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of use or handling.

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor and mists below the applicable workplace exposure limits (Occupational Exposure Limits-OELs) indicated above.

Personal protection equipment

Eye and face protection:

Safety goggles or glasses, or appropriate eye protection.

Skin and body protection:

Select glove material impermeable and resistant to the substance. Wear appropriate clothing to prevent any possibility of skin contact. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Always seek advice from glove suppliers. For continuous contact we recommend nitrile gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified.

Page 4 of 10

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.05.2017 Page 5 of 10

Revision date: 09.14.2020

Security Coat

Respiratory protection:

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

Use a NIOSH/MSHA approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. Comply with the OSHA respirator regulations found in 29 CFR 1910.134.

General hygienic measures:

Avoid contact with skin, eyes and clothing.

Wash hands before breaks and at the end of work.

Wash contaminated clothing before reuse.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Blue/Gray Liquid
Odor	Slight Latex/Ammonia
Odor threshold	Not determined or not available.
pH	Not determined or not available.
Melting point/freezing point	0°C (32°F)
Initial boiling point/range	100°C (212°F)
Flash point (closed cup)	Not determined or not available.
Evaporation rate	<1 (n-Butyl acetate = 1)
Flammability (solid, gas)	Not determined or not available.
Upper flammability/explosive limit	Not determined or not available.
Lower flammability/explosive limit	Not determined or not available.
Vapor pressure	Not determined or not available.
Vapor density	Not determined or not available.
Density	Not determined or not available.
Relative density	0.98
Solubilities	Miscible in water.
Partition coefficient (n-octanol/water)	Not determined or not available.
Auto/Self-ignition temperature	Not determined or not available.
Decomposition temperature	Not determined or not available.
Dynamic viscosity	Not determined or not available.
Kinematic viscosity	270 cm2/s (room temperature) [27,000 cps]
Explosive properties	Not determined or not available.
Oxidizing properties	Not determined or not available.

Other information

voc	0.7 g/L
-----	---------

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.05.2017 Page

Revision date: 09.14.2020

Security Coat

SECTION 10: Stability and reactivity

Reactivity:

Does not react under normal conditions of use and storage.

Chemical stability:

Stable under normal conditions of use and storage.

Possibility of hazardous reactions:

None under normal conditions of use and storage.

Conditions to avoid:

None known.

Incompatible materials:

None known.

Hazardous decomposition products:

None known.

SECTION 11: Toxicological information

Acute toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Route	Result
Bounded Carbon Black	oral	LD50 Rat: >15,400 mg/kg
	dermal	LD50 Rabbit: >3000 mg/kg
Methanol	oral	LDLo - Human - 143 mg/kg
	dermal	LDLo - Monkey - 393 mg/kg
	inhalation	LCLo - Mouse - 64,000 ppm/4 h

Skin corrosion/irritation

Assessment: Based on available data, the classification criteria are not met.

Product data:No data available.

Substance data: No data available.

Serious eye damage/irritation

Assessment: Based on available data, the classification criteria are not met.

Product data:No data available.

Substance data: No data available.
Respiratory or skin sensitization

Assessment: Based on available data, the classification criteria are not met.

Product data:No data available.

Substance data: No data available.

Carcinogenicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Page 6 of 10

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.05.2017 Page 7 of 10

Revision date: 09.14.2020

Security Coat

Substance data:

Name	Species	Result
Bounded Carbon Black		The IARC carcinogenic classification and California Proposition 65 Warning only apply to airborne, unbound particles of respirable size of Carbon Black.
		The carcinogenic classification only applies to airborne, unbound particles of respirable size.

International Agency for Research on Cancer (IARC):

Name	Classification
Bounded Carbon Black	Group 2B - Possibly carcinogenic to humans

National Toxicology Program (NTP): None of the ingredients are listed.

Germ cell mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product data:No data available.

Substance data: No data available.

Reproductive toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:No data available.

Substance data: No data available.

Specific target organ toxicity (single exposure)

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available. Substance data:

Name	Result
Poly (ethylene oxide)	May cause respiratory irritation to organs through single exposure.
Methanol	Component affects the optic nerve.

Specific target organ toxicity (repeated exposure)

Assessment: Based on available data, the classification criteria are not met.

Product data:No data available.

Substance data: No data available.

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:No data available.

Substance data: No data available.

Information on likely routes of exposure:

No data available.

Symptoms related to the physical, chemical and toxicological characteristics:

Refer to Section 4 of this SDS.

Other information:

No data available.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.05.2017 Page

Revision date: 09.14.2020

Security Coat

SECTION 12: Ecological information

Acute (short-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data: No data available.

Chronic (long-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data: No data available.

Persistence and degradability

Product data: No data available.

Substance data:

Name	Result
Bounded Carbon Black	The substance will not be biodegraded.

Bioaccumulative potential

Product data: No data available.

Substance data:

Name	Result
Bounded Carbon Black	Bioaccumulation is not expected to occur.

Mobility in soil

Product data: No data available.
Substance data: No data available.
Other adverse effects: No data available.

SECTION 13: Disposal considerations

Disposal methods:

Dispose in accordance with all applicable regulations. It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities

SECTION 14: Transport information

United States Transportation of dangerous goods (49 CFR DOT)

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

International Maritime Dangerous Goods (IMDG)

_	·
UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

Page 8 of 10

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.05.2017 Page 9 of 10

Revision date: 09.14.2020

Security Coat

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

SECTION 15: Regulatory information

United States regulations

Inventory listing (TSCA): All ingredients are listed or exempt.

Significant New Use Rule (TSCA Section 5): None of the ingredients are listed.

Export notification under TSCA Section 12(b): None of the ingredients are listed.

SARA Section 302 extremely hazardous substances: None of the ingredients are listed.

SARA Section 313 toxic chemicals:

25322-68-3	, (,,	Not Listed
67-56-1	Methanol	Listed
1333-86-4		Not Listed

CERCLA:

67-56-1 Methanol Listed 5000

RCRA:

Section 112(r) of the Clean Air Act (CAA): None of the ingredients are listed.

Massachusetts Right to Know:

1333-86-4	Bounded Carbon Black	Listed
25322-68-3		Not Listed
67-56-1	Methanol	Listed

New Jersey Right to Know:

25322-68-3	Poly (ethylene oxide)	Not Listed
1333-86-4	Bounded Carbon Black	Listed
67-56-1	Methanol	Listed

New York Right to Know:

67-56-1	Methanol	Listed
25322-68-3	Poly (ethylene oxide)	Not Listed
1333-86-4	Bounded Carbon Black	Not Listed

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.05.2017 Page 10 of 10

Revision date: 09.14.2020

Security Coat

Pennsylvania Right to Know:

25322-68-3	Poly (ethylene oxide)	Not Listed
1333-86-4	Bounded Carbon Black	Listed
67-56-1	Methanol	Listed

California Proposition 65:

▲WARNING: This product can expose you to Methanol; which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

Abbreviations and Acronyms: None

Disclaimer:

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

NFPA: 0-0-0 HMIS: 0-0-0

Initial preparation date: 10.05.2017

Revision date: 09.14.2020

End of Safety Data Sheet