SAFETY DATA SHEET

1. Identification

Product number SP780

Product identifier 3D INSTANT SHINE

Revision date 05-27-2014

Company information 3D INTERNATIONAL LLC

20724 CENTRE POINTE PARKWAY UNIT 1 SANTA CLARITA, CA 91350 United States

 Company phone
 1-888-999-7627

 Emergency telephone US
 1-866-836-8855

 Emergency telephone outside
 1-952-852-4646

US

Version # 02

Supersedes date04-28-2014Recommended useProtective CoatingRecommended restrictionsNone known.

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1 **Health hazards** Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 2A Germ cell mutagenicity Category 1B Carcinogenicity Category 1B Reproductive toxicity (fertility) Category 2 Specific target organ toxicity, repeated Category 2

exposure

Aspiration hazard Category 1

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation.

Causes serious eye irritation. May cause genetic defects. May cause cancer. Suspected of damaging fertility. May cause damage to organs through prolonged or repeated exposure.

PreventionObtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not

and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn,

even after use. Do not breathe gas. Wash thoroughly after handling. Wear protective

gloves/protective clothing/eye protection/face protection.

Response If swallowed: Immediately call a poison center/doctor. If on skin: Wash with plenty of water. If in

eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Specific treatment (see this label). Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash

before reuse.

Storage Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

Not classified.

Environmental hazards Hazardous to the aquatic environment, acute Category 3

hazard

Product name: Interior Detailer Vinyl

SDS US

Hazardous to the aquatic environment,

long-term hazard

Supplemental information

Hazard statement Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

Prevention Avoid release to the environment.

72.4% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 72.4% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Butane		106-97-8	20 - 40
Naphtha (petroleum), hydrotreated light		64742-49-0	20 - 40
Propane		74-98-6	20 - 40
n-Hexane		110-54-3	10 - 20
Acetone		67-64-1	2.5 - 10
Polydimethylsiloxane		63148-62-9	2.5 - 10
Cyclohexane		110-82-7	0.1 - 1
Other components below reportable level	s		0.1 - 1

^{#:} This substance has workplace exposure limit(s).

4. First-aid measures

Inhalation If symptoms develop move victim to fresh air. Call a physician if symptoms develop or persist. Skin contact

Remove contaminated clothing. Wash off with soap and plenty of water. If skin irritation occurs:

Get medical advice/attention. Wash clothing separately before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Call a physician or poison control center immediately. Rinse mouth, Do not induce vomiting, If

Category 3

vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Aspiration may cause pulmonary edema and pneumonitis. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way

valve or other proper respiratory medical device.

Most important symptoms/effects, acute and delayed

Irritation of eyes and mucous membranes. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Aspiration may cause pulmonary edema and pneumonitis. Skin irritation. Prolonged exposure may cause chronic effects. Causes serious eye irritation.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information

media

Ingestion

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire-fighting equipment/instructions

Specific methods

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Use standard firefighting procedures and consider the hazards of other involved materials. Move container from fire area if it can be done without risk. In the event of fire and/or explosion do not breathe fumes.

Product name: Interior Detailer Vinvl

SDS US Product #: 780-000 Version #: 02 Revision date: 05-27-2014 Issue date: 04-28-2014

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the MSDS.

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Collect spillage. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the MSDS.

Environmental precautions

Environmental manager must be informed of all major releases. Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle or store near an open flame, heat or other sources of ignition. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Avoid contact with skin, eyes and clothing. Use non-sparking tools and explosion-proof equipment. Do not re-use empty containers. Do not breathe gas. Do not taste or swallow. Avoid contact with skin. Avoid contact with eyes. Avoid contact during pregnancy/while nursing. Avoid prolonged exposure. Use only in well-ventilated areas. Use personal protective equipment as required. Observe good industrial hygiene practices. When using, do not eat, drink or smoke. Wash thoroughly after handling. Do not empty into drains.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the MSDS). Level 2 Aerosol.

8. Exposure controls/personal protection

Occupational exposure limits

.1000)
)

Components	Туре	Value	
Acetone (CAS 67-64-1)	PEL	2400 mg/m3	
		1000 ppm	
Cyclohexane (CAS 110-82-7)	PEL	1050 mg/m3	
		300 ppm	
n-Hexane (CAS 110-54-3)	PEL	1800 mg/m3	
		500 ppm	
Propane (CAS 74-98-6)	PEL	1800 mg/m3	
		1000 ppm	
US. ACGIH Threshold Limit Value	s		
Components	Type	Value	
Acetone (CAS 67-64-1)	STEL	750 ppm	
	TWA	500 ppm	
Cyclohexane (CAS 110-82-7)	TWA	100 ppm	
n-Hexane (CAS 110-54-3)	TWA	50 ppm	
US. NIOSH: Pocket Guide to Cher	nical Hazards		
Components	Type	Value	
Acetone (CAS 67-64-1)	TWA	590 mg/m3	
		250 ppm	
Butane (CAS 106-97-8)	TWA	1900 mg/m3	

Product name: Interior Detailer Vinyl

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Туре	Value	
		800 ppm	
Cyclohexane (CAS 110-82-7)	TWA	1050 mg/m3	
,		300 ppm	
n-Hexane (CAS 110-54-3)	TWA	180 mg/m3	
		50 ppm	
Propane (CAS 74-98-6)	TWA	1800 mg/m3	
		1000 ppm	

Biological limit values

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	50 mg/l	Acetone	Urine	*
n-Hexane (CAS 110-54-3)	0.4 mg/l	2,5-Hexanedio n, without hydrolysis	Urine	*

^{* -} For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

n-Hexane (CAS 110-54-3) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

n-Hexane (CAS 110-54-3) Can be absorbed through the skin.

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear eye/face protection. Wear safety glasses with side shields (or goggles).

Hand protection Wear protective gloves.

Other Wear appropriate chemical resistant clothing.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

> limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. If permissible levels are exceeded use

NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely

wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance Compressed liquefied gas.

Color Colorless. Form Aerosol. Physical state Gas.

Boiling point 69.8 °F (21 °C) estimated

Flash point -156.00 °F (-104.44 °C) Propellant estimated

Not available. Melting point/freezing point

Odor fruity

Not Applicable estimated pН

Solubility(ies) Not available. Vapor density Not available.

34 - 45 psig @70F estimated Vapor pressure

Not available. Viscosity

Other information

Specific gravity 0.629 estimated estimated

10. Stability and reactivity

Product name: Interior Detailer Vinvl

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

Hazardous polymerization does not occur.

Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Ingestion May be fatal if swallowed and enters airways.

Inhalation May be fatal if swallowed and enters airways. Prolonged inhalation may be harmful. May cause

damage to organs by inhalation.

Skin contact Causes skin irritation.

Eye contact Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Irritant effects.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

Additionally	may be latar in estamented and enter	io all mayo.
Product	Species	Test Results
Interior Detailer Vinyl (CAS Mix	xture)	
Acute		
Dermal		
LD50	Rat	6307 mg/kg
Inhalation		
LC50	Mouse	2893.6169 mg/l, 2 Hours, estimated
	Rat	5444.7056 mg/l, 15 Minutes, estimated
		2800 mg/l, 4 Hours, estimated
		322 mg/l/4h
Oral		
LD50	Rat	207.6246 mg/kg, estimated
	Wistar rat	423.9226 mg/kg, estimated
Other		
LD50	Mouse	1883.9171 ml/kg, estimated
	Rat	19444.6191 mg/kg, estimated
Components	Species	Test Results
Acetone (CAS 67-64-1)	·	
Acute		
Dermal		
LD50	Rabbit	20000 mg/kg
		20 ml/kg
Inhalation		
LC50	Rat	76 mg/l, 4 Hours
		50.1 mg/l, 8 Hours
Oral		
LD50	Mouse	3000 mg/kg
	Rabbit	5340 mg/kg
	Rat	5800 mg/kg
Other		
LD50	Mouse	1297 mg/kg
	Rat	5500 mg/kg
Butane (CAS 106-97-8)		5 5
Acute		
Inhalation		
LC50	Mouse	680 mg/l, 2 Hours

Product name: Interior Detailer Vinyl

SDS US

Product #: 780-000 Version #: 02 Revision date: 05-27-2014 Issue date: 04-28-2014

Components	Species	Test Results
	Rat	658 mg/l, 4 Hours
Cyclohexane (CAS 110-82-7	")	
Acute		
Inhalation		
NOEL	Monkey	1243 mg/l, 6 Hours
Oral		
LD50	Mouse	1300 mg/kg
	Rat	29820 mg/kg
n-Hexane (CAS 110-54-3)		
Acute		
Inhalation		
LC50	Mouse	48000 mg/l, 4 Hours
Oral		
LD50	Rat	24 g/kg
	Wistar rat	49 g/kg
Propane (CAS 74-98-6)		
Acute		
Inhalation		
LC50	Rat	> 1442.847 mg/l, 15 Minutes
		658 mg/l/4h

^{*} Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory sensitization Not available.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity May cause genetic defects.

Carcinogenicity May cause cancer.

Reproductive toxicity Suspected of damaging fertility.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Respiratory system. Central nervous system. Peripheral nervous system. May cause damage to

organs through prolonged or repeated exposure.

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects. May cause

damage to organs through prolonged or repeated exposure.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects. Accumulation in aquatic organisms is expected.

Product		Species	Test Results
Interior Detailer Vinyl	(CAS Mixture)		
Algae	IC50	Algae	13021 mg/L, 72 Hours
Crustacea	EC50	Daphnia	1591 mg/L, 48 Hours
Fish	LC50	Fish	23.6766 mg/L, 96 Hours
Components		Species	Test Results
Acetone (CAS 67-64-	1)		
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	21.6 - 23.9 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours
Cyclohexane (CAS 11	0-82-7)		
Aquatic			
Fish	LC50	Fathead minnow (Pimephales promelas)	23.03 - 42.07 mg/l, 96 hours

Product name: Interior Detailer Vinyl

Product #: 780-000 Version #: 02 Revision date: 05-27-2014 Issue date: 04-28-2014

Components Species Test Results

Polydimethylsiloxane (CAS 63148-62-9)

Aquatic

Fish LC50 Channel catfish (Ictalurus punctatus) 2.36 - 4.15 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

 Acetone
 -0.24

 Propane
 2.36

 Butane
 2.89

 Cyclohexane
 3.44

 n-Hexane
 3.9

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste codeThe waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

US RCRA Hazardous Waste U List: Reference

Acetone (CAS 67-64-1) U002 Cyclohexane (CAS 110-82-7) U056

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

UN number UN1950

UN proper shipping name Aerosols, flammable

Transport hazard class(es) 2.1

Subsidiary class(es)Not available.Packing groupNot available.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Labels requiredNoneSpecial provisionsN82Packaging exceptions306Packaging non bulkNonePackaging bulkNone

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

IATA

UN number UN1950

UN proper shipping name Aerosols, flammable

Transport hazard class(es) 2.1 Subsidiary class(es) -

Packaging group Not available.

Environmental hazards No Labels required 2.1 ERG Code 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Packaging Exceptions LTD QTY

^{*} Estimates for product may be based on additional component data not shown.

IMDG

UN1950 **UN** number **AEROSOLS UN** proper shipping name

Transport hazard class(es) 2.1 Subsidiary class(es)

Not available. **Packaging group**

Environmental hazards

Marine pollutant Nο None Labels required

EmS Not available.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to

Not applicable.

LTD QTY

Annex II of MARPOL 73/78 and the IBC Code

Packaging Exceptions

DOT



IATA; IMDG



15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS 67-64-1) LISTED Cyclohexane (CAS 110-82-7) LISTED n-Hexane (CAS 110-54-3) LISTED

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

SARA 304 Emergency release notification

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

> Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

SARA 302 Extremely

No

hazardous substance SARA 311/312 Hazardous

No

chemical

Product name: Interior Detailer Vinyl

SDS US

Product #: 780-000 Version #: 02 Revision date: 05-27-2014 Issue date: 04-28-2014

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

n-Hexane (CAS 110-54-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

Safe Drinking Water Act

Not regulated.

(SDWA)

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and **Chemical Code Number**

Acetone (CAS 67-64-1) 6532

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1) 35 % weight/volumn

DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1) 6532

Food and Drug Not regulated.

Administration (FDA)

US state regulations WARNING: This product contains a chemical known to the State of California to cause cancer.

US. New Jersey Worker and Community Right-to-Know Act

500 lbs Butane (CAS 106-97-8) Cyclohexane (CAS 110-82-7) 500 lbs 500 lbs n-Hexane (CAS 110-54-3) Propane (CAS 74-98-6) 500 lbs

Inventory name

US. Pennsylvania RTK - Hazardous Substances

Acetone (CAS 67-64-1) Butane (CAS 106-97-8) Cyclohexane (CAS 110-82-7) n-Hexane (CAS 110-54-3) Propane (CAS 74-98-6)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reprodu harm.

International Inventories

Country(s) or region

Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s)

16. Other information, including date of preparation or last revision

Issue date 04-28-2014 **Revision date** 05-27-2014

Version # 02

Further information Not available.

Product #: 780-000 Version #: 02 Revision date: 05-27-2014 Issue date: 04-28-2014

On inventory (yes/no)*

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Product name: Interior Detailer Vinyl

Product #: 780-000 Version #: 02 Revision date: 05-27-2014 Issue date: 04-28-2014