SAFETY DATA SHEET

1. Identification

Product identifier BG Battery Cleaner—Acid Detector (Aerosol)

Other means of identification

Formula number 1 485 **Product code**

Synonyms P485-xxxx Recommended use Not available. None known. Recommended restrictions

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

BG Products, Inc. Company name **Address** 740 S. Wichita St. Wichita, KS 67213

United States

316-266-8120 Telephone Website www.bgprod.com E-mail msds@bgprod.com Contact person **Product Stewardship Emergency phone number** (800) 424-9300 (CHEMTREC)

2. Hazard(s) identification

Flammable aerosols Category 1 Physical hazards

> Liquefied gas Gases under pressure Serious eye damage/eye irritation Category 2

Environmental hazards Not classified. **OSHA** defined hazards Not classified.

Label elements

Health hazards



Signal word Danger

Hazard statement Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes

serious eye irritation.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open

flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

Wash thoroughly after handling. Wear eye protection/face protection.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and Response

easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Storage Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding

50°C/122°F.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information 12% of the mixture consists of component(s) of unknown acute oral toxicity. 12% of the mixture

consists of component(s) of unknown acute dermal toxicity. 15% of the mixture consists of

component(s) of unknown long-term hazards to the aquatic environment.

Material name: BG Battery Cleaner—Acid Detector (Aerosol)

SDS US 485 Version #: 6.0 Revision date: 12-01-2021 Issue date: 07-30-2020

3. Composition/information on ingredients

Mixtures

Ingestion

media

Chemical name	Common name and synonyms	CAS number	%
Butane		106-97-8	10 - 20
ISOPROPANOL		67-63-0	3 - 5
Propane		74-98-6	1 - 3

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Wash off with soap and water. Get medical attention if irritation develops and persists. Skin contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Not likely, due to the form of the product. In the unlikely event of swallowing contact a physician or

poison control center. Rinse mouth.

Most important symptoms/effects, acute and Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

delayed

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire fighting equipment/instructions In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not

General fire hazards

Extremely flammable aerosol. Contents under pressure. Pressurized container may explode when exposed to heat or flame.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

breathe fumes.

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Close valve after each use and when empty. Protect containers from physical damage; do not drag, roll, slide, or drop. When moving containers, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport containers. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Purge air from system before introducing gas. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Do not re-use empty containers. Avoid contact with eyes. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in tightly closed container. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Components	Туре	Value	
ISOPROPANOL (CAS 67-63-0)	PEL	980 mg/m3	
		400 ppm	
Propane (CAS 74-98-6)	PEL	1800 mg/m3	
		1000 ppm	
US. ACGIH Threshold Limit Valu	es		
Components	Туре	Value	
Butane (CAS 106-97-8)	STEL	1000 ppm	
ISOPROPANOL (CAS 67-63-0)	STEL	400 ppm	
	TWA	200 ppm	
US. NIOSH: Pocket Guide to Che	emical Hazards		
Components	Туре	Value	
Butane (CAS 106-97-8)	TWA	1900 mg/m3	
		800 ppm	
ISOPROPANOL (CAS 67-63-0)	STEL	1225 mg/m3	
		500 ppm	
	TWA	980 mg/m3	
		400 ppm	
Propane (CAS 74-98-6)	TWA	1800 mg/m3	
		1000 ppm	

SDS US

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
ISOPROPANOL (CAS 67-63-0)	40 mg/l	Acetone	Urine	*

^{* -} For sampling details, please see the source document.

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves.Other Wear appropriate chemical resistant clothing.

Respiratory protection If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an

air-supplied respirator.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid.

Form Aerosol. Liquefied gas.

Color Not available.
Odor Not available.
Odor threshold Not available.
pH Not available.

Melting point/freezing point -216.76 °F (-138.2 °C) estimated

Initial boiling point and boiling

range

212 °F (100 °C)

Flash point -76.0 °F (-60.0 °C) estimated

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

lammability limit - lower 1.9

1.9 % estimated

(%)

Flammability limit - upper

%)

8.5 % estimated

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 258.39 hPa estimated

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 548.6 °F (287 °C) estimated

Decomposition temperature Not available. **Viscosity** Not available.

Other information

Density 0.94 g/cm3 estimated

Explosive properties Not explosive.

Flammability class Flammable IB estimated
Heat of combustion (NFPA 6.03 kJ/g estimated

30B)

Oxidizing properties

Percent volatile

Specific gravity

VOC

Not oxidizing.

86.91 % estimated

0.94159 estimated

3 % estimated

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Heat. Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materialsStrong oxidizing agents. Chlorine. Fluorine. Nitrates.Hazardous decompositionNo hazardous decomposition products are known.

products

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contactNo adverse effects due to skin contact are expected.

Eye contact Causes serious eye irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision.

Information on toxicological effects

Acute toxicity Not known.

Components Species Test Results

ISOPROPANOL (CAS 67-63-0)

Acute Dermal

LD50 Rabbit 12800 mg/kg

Oral

LD50 Rat 4.7 g/kg

Skin corrosion/irritationBased on available data, the classification criteria are not met.

Serious eye damage/eye Causes serious eye irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

EcotoxicityThe product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components Species Test Results

ISOPROPANOL (CAS 67-63-0)

Aquatic Acute

Fish LC50 Bluegill (Lepomis macrochirus) > 1400 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

 Butane
 2.89

 ISOPROPANOL
 0.05

 Propane
 2.36

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Incinerate the material under controlled conditions in an approved incinerator. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international

regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code D001: Waste Flammable material with a flash point <140 F

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

14. Transport information

DOT

UN number UN1950

UN proper shipping name Aerosols, flammable, (each not exceeding 1 L capacity)

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not available.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions N82
Packaging exceptions 306
Packaging non bulk None

Packaging bulk None

IATA

UN number UN1950

UN proper shipping name Aerosols, flammable Transport hazard class(es)

Class 2.1 Subsidiary risk -

Packing group Not available.

Environmental hazards No. **ERG Code** 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

Allowed with restrictions.

aircraft

Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN1950
UN proper shipping name AEROSOLS
Transport hazard class(es)

Class 2 Subsidiary risk -

Packing group Not available.

Environmental hazards

Marine pollutant No. EmS F-D, S-U

Transport in bulk according to Annex II of MARPOL 73/78 and

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Not established.

DOT

the IBC Code



IATA; IMDG



General information

Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: Ensure that containers are firmly secured. Ensure cylinder valve is closed and not leaking. Ensure valve outlet cap nut or plug (where provided) is correctly fitted. Ensure valve protection device (where provided) is correctly fitted. Ensure adequate ventilation. Ensure compliance with applicable regulations.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

All components of the mixture on the TSCA 8(b) inventory are designated

"active".

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Butane (CAS 106-97-8)
ISOPROPANOL (CAS 67-63-0)
Propane (CAS 74-98-6)
Listed.
Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Yes

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

Classified hazard Flammable (gases, aerosols, liquids, or solids)

categories Gas under pressure

Serious eye damage or eye irritation

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
ISOPROPANOL	67-63-0	3 - 5	

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

Safe Drinking Water Act Not regulated.

(SDWA)

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

ISOPROPANOL (CAS 67-63-0) Low priority

US state regulations

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Butane (CAS 106-97-8) ISOPROPANOL (CAS 67-63-0)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes

Material name: BG Battery Cleaner—Acid Detector (Aerosol)

SDS US

Country(s) or region On inventory (yes/no)* Inventory name

Korea Existing Chemicals List (ECL) New Zealand **New Zealand Inventory** Yes

Philippine Inventory of Chemicals and Chemical Substances **Philippines**

(PICCS)

Taiwan Taiwan Chemical Substance Inventory (TCSI) Yes United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

country(s).

16. Other information, including date of preparation or last revision

07-30-2020 Issue date 12-01-2021 **Revision date**

Version # 6.0

BG Products, Inc. cannot anticipate all conditions under which this information and its product, or Disclaimer

the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the

sheet was written based on the best knowledge and experience currently available.

Revision information Product and Company Identification: Product and Company Identification

> Hazard(s) identification: Hazard statement Hazard(s) identification: Prevention

Composition / Information on Ingredients: Disclosure Overrides

First-aid measures: First Aid Equipment

Accidental release measures: Personal precautions for emergency responders Accidental release measures: Personal precautions for non-emergency personnel

Physical & Chemical Properties: Multiple Properties

GHS: Classification

Material name: BG Battery Cleaner—Acid Detector (Aerosol)

Yes