

SAFETY DATA SHEET

1. Identification

Product number 1000036093
Product identifier **NAPA MACS BRAKE CLEANER 4800**
Revision date 08-30-2018
Company information NAPA BALKAMP
2601 Stout Heritage Parkway
Plainfield, In 46168 United States
Company phone General Assistance 1-317-754-3900
Emergency telephone US 1-866-836-8855
Emergency telephone outside US 1-952-852-4646
Version # 02
Supersedes date 08-30-2018
Recommended use CLEANER
Recommended restrictions None known.

2. Hazard(s) identification

Physical hazards	Flammable aerosols	Category 1
Health hazards	Acute toxicity, oral	Category 3
	Acute toxicity, dermal	Category 3
	Acute toxicity, inhalation	Category 4
	Skin corrosion/irritation	Category 2
	Reproductive toxicity (fertility, the unborn child)	Category 2
	Specific target organ toxicity, single exposure	Category 1
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 2
	Aspiration hazard	Category 1
OSHA defined hazards	Not classified.	

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. Toxic if swallowed. May be fatal if swallowed and enters airways. Toxic in contact with skin. Causes skin irritation. Harmful if inhaled. May cause drowsiness or dizziness. Suspected of damaging the unborn child. Suspected of damaging fertility. Causes damage to organs. May cause damage to organs through prolonged or repeated exposure.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Response	If swallowed: Immediately call a poison center/doctor. Rinse mouth. Do NOT induce vomiting. If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If exposed: Call a poison center/doctor. If exposed or concerned: Get medical advice/attention. If skin irritation occurs: Get medical advice/attention. Take off immediately all contaminated clothing and wash it before reuse.	
Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.	
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.	
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 2
	Hazardous to the aquatic environment, long-term hazard	Category 2
Hazard(s) not otherwise classified (HNOC)	None known.	
Supplemental information	None.	

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Methanol		67-56-1	20 - 40
Naphtha, (Petroleum), Hydrotreated Light		64742-49-0	20 - 40
n-Heptane		142-82-5	10 - 20
Acetone		67-64-1	2.5 - 10
Carbon Dioxide		124-38-9	2.5 - 10
Toluene		108-88-3	2.5 - 10
Methylcyclohexane		108-87-2	1 - 2.5
Other components below reportable levels			0.1 - 1

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Take off immediately all contaminated clothing. Wash with plenty of soap and water. Get medical advice/attention if you feel unwell. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	Take off immediately all contaminated clothing. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media	Alcohol resistant foam. Powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent entry into waterways, sewer, basements or confined areas. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe gas. Do not taste or swallow. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Level 2 Aerosol. Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Acetone (CAS 67-64-1)	PEL	2400 mg/m3 1000 ppm
Carbon Dioxide (CAS 124-38-9)	PEL	9000 mg/m3
Methanol (CAS 67-56-1)	PEL	5000 ppm 260 mg/m3 200 ppm

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Methylcyclohexane (CAS 108-87-2)	PEL	2000 mg/m3
n-Heptane (CAS 142-82-5)	PEL	500 ppm 2000 mg/m3 500 ppm

US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
Toluene (CAS 108-88-3)	Ceiling TWA	300 ppm 200 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
Acetone (CAS 67-64-1)	STEL TWA	500 ppm 250 ppm
Carbon Dioxide (CAS 124-38-9)	STEL	30000 ppm
Methanol (CAS 67-56-1)	TWA STEL TWA	5000 ppm 250 ppm 200 ppm
Methylcyclohexane (CAS 108-87-2)	TWA	400 ppm
n-Heptane (CAS 142-82-5)	STEL TWA	500 ppm 400 ppm
Toluene (CAS 108-88-3)	TWA	20 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Acetone (CAS 67-64-1)	TWA	590 mg/m3 250 ppm
Carbon Dioxide (CAS 124-38-9)	STEL TWA	54000 mg/m3 30000 ppm 9000 mg/m3 5000 ppm
Methanol (CAS 67-56-1)	STEL TWA	325 mg/m3 250 ppm 260 mg/m3 200 ppm
Methylcyclohexane (CAS 108-87-2)	TWA	1600 mg/m3
n-Heptane (CAS 142-82-5)	Ceiling TWA	400 ppm 1800 mg/m3 440 ppm 350 mg/m3 85 ppm
Toluene (CAS 108-88-3)	STEL TWA	560 mg/m3 150 ppm 375 mg/m3 100 ppm

Biological limit values**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	25 mg/l	Acetone	Urine	*
Methanol (CAS 67-56-1)	15 mg/l	Methanol	Urine	*

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*

* - For sampling details, please see the source document.

Exposure guidelines**US - California OELs: Skin designation**

Methanol (CAS 67-56-1)	Can be absorbed through the skin.
Toluene (CAS 108-88-3)	Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Methanol (CAS 67-56-1)	Skin designation applies.
Toluene (CAS 108-88-3)	Skin designation applies.

US - Tennessee OELs: Skin designation

Methanol (CAS 67-56-1)	Can be absorbed through the skin.
------------------------	-----------------------------------

US ACGIH Threshold Limit Values: Skin designation

Methanol (CAS 67-56-1)	Can be absorbed through the skin.
------------------------	-----------------------------------

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Methanol (CAS 67-56-1)	Can be absorbed through the skin.
------------------------	-----------------------------------

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties**Appearance**

Physical state Gas.

Form Aerosol.

Color Not available.

Odor Not available.

Odor threshold Not available.

pH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling range 174.67 °F (79.26 °C) estimated

Flash point 29.3 °F (-1.5 °C) estimated

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower (%)	3.3 % estimated
Flammability limit - upper (%)	18.9 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.

Vapor pressure 75 - 95 psig @70F estimated
120 - 140 psig @130F estimated

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

Explosive properties Not explosive.

Oxidizing properties Not oxidizing.

Specific gravity 0.806 estimated

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous reactions Hazardous polymerization does not occur.

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Acids. Strong oxidizing agents. Aluminum.

Hazardous decomposition products No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Harmful if inhaled. May cause damage to organs by inhalation. May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting.

Skin contact Toxic in contact with skin. Causes skin irritation.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Toxic if swallowed. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways. Toxic in contact with skin. Harmful if inhaled. Narcotic effects.

Components	Species	Test Results
Acetone (CAS 67-64-1)		
Acute		
Dermal		
LD50	Guinea pig	> 7426 mg/kg, 24 Hours > 9.4 ml/kg, 24 Hours

Components	Species	Test Results
	Rabbit	> 7426 mg/kg, 24 Hours > 9.4 ml/kg, 24 Hours
Inhalation		
LC50	Rat	55700 ppm, 3 Hours 132 mg/l, 3 Hours 50.1 mg/l
Oral		
LD50	Rat	5800 mg/kg 2.2 ml/kg
Methanol (CAS 67-56-1)		
Acute		
Inhalation		
LC50	Cat	85.41 mg/l, 4.5 Hours 43.68 mg/l, 6 Hours
	Mouse	79.43 mg/l, 134 Minutes
	Rat	> 115.9 mg/l, 4 Hours 82.1 mg/l, 6 Hours
Oral		
LD50	Monkey	6000 mg/kg
	Pig	> 5000 mg/kg
	Rat	1187 - 2769 mg/kg
Methylcyclohexane (CAS 108-87-2)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg, 24 Hours
Inhalation		
<i>Vapor</i>		
LC100	Rabbit	59.9 mg/l
LC50	Dog	> 4071 ppm, If <1L: Consumer Commodity Hours > 16.3 mg/l, If <1L: Consumer Commodity Hours
	Mouse	> 6564 ppm, If <1L: Consumer Commodity Hours > 26.3 mg/l, If <1L: Consumer Commodity Hours
	Rat	> 6564 ppm, If <1L: Consumer Commodity Hours > 26.3 mg/l, If <1L: Consumer Commodity Hours
LC50	Rat	16 mg/l, 4 Hours
Naphtha, (Petroleum), Hydrotreated Light (CAS 64742-49-0)		
Acute		
Dermal		
LD50	Guinea pig; Rabbit	> 9.4 ml/kg, 24 Hours
	Rabbit	> 1900 mg/kg, 24 Hours
Inhalation		
LC50	Rat	> 5000 mg/m3, 4 Hours > 4980 mg/m3

Components	Species	Test Results
		> 4980 mg/m3, 4 Hours
		> 4.96 mg/l, 4 Hours
		13700 ppm, 4 Hours
Oral		
LD50	Rat	4820 mg/kg
n-Heptane (CAS 142-82-5)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg, 24 Hours
Inhalation		
LC50	Rat	> 29.29 mg/l, 4 Hours
Oral		
LD50	Rat	> 5000 mg/kg
Toluene (CAS 108-88-3)		
Acute		
Dermal		
LD50	Rabbit	> 5000 mg/kg, 24 Hours
Inhalation		
LC50	Mouse	6405 - 7436 ppm, 6 Hours
		5320 ppm, 8 Hours
	Rat	5879 - 6281 ppm, 6 Hours
		25.7 mg/l, 4 Hours
Oral		
LD50	Rat	> 5000 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.
Respiratory or skin sensitization	
Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.
IARC Monographs. Overall Evaluation of Carcinogenicity	
Toluene (CAS 108-88-3)	3 Not classifiable as to carcinogenicity to humans.
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)	
	Not regulated.
US. National Toxicology Program (NTP) Report on Carcinogens	
	Not listed.
Reproductive toxicity	Suspected of damaging fertility. Suspected of damaging the unborn child.
Specific target organ toxicity - single exposure	Causes damage to organs. May cause drowsiness and dizziness.
Specific target organ toxicity - repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	May be fatal if swallowed and enters airways.
Chronic effects	May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Components		Species	Test Results
Acetone (CAS 67-64-1)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	21.6 - 23.9 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours
Methanol (CAS 67-56-1)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	> 10000 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	> 100 mg/l, 96 hours
Methylcyclohexane (CAS 108-87-2)			
Aquatic			
Fish	LC50	Striped bass (Morone saxatilis)	5.8 mg/l, 96 hours
n-Heptane (CAS 142-82-5)			
Aquatic			
Fish	LC50	Mozambique tilapia (Tilapia mossambica)	375 mg/l, 96 hours
Toluene (CAS 108-88-3)			
Aquatic			
Algae	IC50	Algae	433.0001 mg/L, 72 Hours
Crustacea	EC50	Daphnia	7.645 mg/L, 48 Hours
		Water flea (Daphnia magna)	5.46 - 9.83 mg/l, 48 hours
Fish	LC50	Coho salmon,silver salmon (Oncorhynchus kisutch)	8.11 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Acetone	-0.24
Methanol	-0.77
Methylcyclohexane	3.61
n-Heptane	4.66
Toluene	2.73

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

DOT

UN number	UN1950
UN proper shipping name	Aerosols, flammable, (each not exceeding 1 L capacity)
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking.

IATA

UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	Yes
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.
Packaging Exceptions	LTD QTY

IMDG

UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	None
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	Yes
EmS	F-D, S-U
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Packaging Exceptions	LTD QTY
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.


DOT



IATA; IMDG



Marine pollutant



General information

DOT Regulated Marine Pollutant. IMDG Regulated Marine Pollutant.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS 67-64-1)

Listed.

Methanol (CAS 67-56-1)

Listed.

Toluene (CAS 108-88-3)

Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - Yes

Delayed Hazard - Yes

Fire Hazard - Yes

Pressure Hazard - Yes

Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical

No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Methanol	67-56-1	20 - 40

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Toluene	108-88-3	2.5 - 10

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Methanol (CAS 67-56-1)

Toluene (CAS 108-88-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.**Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number**

Acetone (CAS 67-64-1) 6532

Toluene (CAS 108-88-3) 6594

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1) 35 %WV

Toluene (CAS 108-88-3) 35 %WV

DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1) 6532

Toluene (CAS 108-88-3) 594

US state regulations**US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)**

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Acetone (CAS 67-64-1)

Methanol (CAS 67-56-1)

Naphtha, (Petroleum), Hydrotreated Light (CAS 64742-49-0)

Toluene (CAS 108-88-3)

US. Massachusetts RTK - Substance List

Acetone (CAS 67-64-1)

Carbon Dioxide (CAS 124-38-9)

Methanol (CAS 67-56-1)

Methylcyclohexane (CAS 108-87-2)

n-Heptane (CAS 142-82-5)

Toluene (CAS 108-88-3)

US. New Jersey Worker and Community Right-to-Know Act

Acetone (CAS 67-64-1)

Carbon Dioxide (CAS 124-38-9)

Methanol (CAS 67-56-1)

Methylcyclohexane (CAS 108-87-2)

n-Heptane (CAS 142-82-5)

Toluene (CAS 108-88-3)

US. Pennsylvania Worker and Community Right-to-Know Law

Acetone (CAS 67-64-1)

Carbon Dioxide (CAS 124-38-9)

Methanol (CAS 67-56-1)

Methylcyclohexane (CAS 108-87-2)

n-Heptane (CAS 142-82-5)

Toluene (CAS 108-88-3)

US. Rhode Island RTK

Acetone (CAS 67-64-1)

Methanol (CAS 67-56-1)

Toluene (CAS 108-88-3)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Benzene (CAS 71-43-2)	Listed: February 27, 1987
Ethyl Benzene (CAS 100-41-4)	Listed: June 11, 2004

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Benzene (CAS 71-43-2)	Listed: December 26, 1997
Methanol (CAS 67-56-1)	Listed: March 16, 2012
Toluene (CAS 108-88-3)	Listed: January 1, 1991

US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

Benzene (CAS 71-43-2)	Listed: December 26, 1997
-----------------------	---------------------------

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 08-30-2018

Revision date 08-30-2018

Version # 02

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Revision information Hazard(s) identification: Hazard statement
 Hazard(s) identification: Response
 Toxicological information: Inhalation
 Toxicological information: Specific target organ toxicity - single exposure
 GHS: Classification