

Safety Data Sheet

Product Name: TUNNEL FOAMING SS 55 GALL

Product identifier: 507255

Revision Date: 08-19-2016

Replaces:

EVERCOAT®

1. Identification

Product identifier used on the label:

Product Name: TUNNEL FOAMING SS 55 GALL

Product identifier: 507255

Other means of identification

Synonyms: No data available

Recommended use of the chemical and restrictions on use: Used as a cleaner for grease and grime without leaving any residue on the clean

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Chemical Manufacturer /
Importer / Distributor: ITW Evercoat
a division of Illinois Tool Works Inc.
6600 Cornell Road
Cincinnati, OH 45242
513-489-7600

Emergency phone number: CHEMTREC: 1-800-424-9300
CANUTEC: 1-613-996-6666

2. Hazard(s) identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Hazard
Symbols:



GHS Classification: Serious Eye Damage/Eye Irritation Category 1
Skin Corrosion/Irritation Category 2

GHS Signal Word: Danger

GHS Hazard Statements: Causes skin irritation.
Causes serious eye damage.

GHS Precautionary Statements:

Safety Precautions: Wash thoroughly after handling.
Wear protective gloves/protective clothing/eye protection/face protection.

First Aid Measures: IF ON SKIN: Wash with plenty of soap and water.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Safety Data Sheet

Product Name: TUNNEL FOAMING SS 55 GALL

Product identifier: 507255

Revision Date: 08-19-2016

Replaces:

Immediately call a POISON CENTER/doctor
Specific treatment (see on this label).
If skin irritation occurs: Get medical advice/attention.

Hazards not otherwise
classified:

No data available

3. Composition/information on ingredients

Chemical Component:	CAS number and other unique identifiers	% (or range) of ingredient
Sodium metasilicate	6834-92-0	1 - 5
Tetrasodium Ethylenediamine Tetraacetate	64-02-8	0.5 - 1.5

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid measures

Description of necessary measures, subdivided according to the different routes of exposure, i.e., inhalation, skin and eye contact, and ingestion:

Eye Contact: Immediately flush eyes with plenty of water for at least 20 minutes retracting eyelids often. This corrosive material can cause immediate and permanent eye damage. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention and monitor the eye daily as advised by your physician. Flush eye with water for 20 minutes. Get medical attention.

Skin Contact: Wash with soap and water under a drench shower. Remove contaminated clothing, launder immediately, and discard contaminated leather goods. Get medical attention immediately. Wash with soap and water. Get medical attention if irritation develops or persists.

Inhalation: Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. If not breathing, give artificial respiration and have a trained individual administer oxygen. Get medical attention immediately

Ingestion: Corrosive. Do not induce vomiting! Drink one glass of water followed by milk if available. Seek medical attention immediately and give the medical care provider with this MSDS. If swallowed, do NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

Most important symptoms/effects, acute and delayed:

Safety Data Sheet

Product Name: TUNNEL FOAMING SS 55 GALL

Product identifier: 507255

Revision Date: 08-19-2016

Replaces:

Most important symptoms/effects (Acute):	No data available
Most important symptoms/effects (Delayed):	No data available
Indication of immediate medical attention and special treatment needed, if necessary:	No additional first aid information available

5. Fire-fighting measures

Suitable (and unsuitable) extinguishing media:

Suitable extinguishing media: Use alcohol resistant foam, carbon dioxide, or dry chemical when fighting fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the surface of the fire. Do Not direct a stream of water into the hot burning liquid.

Unsuitable extinguishing media: No data available

Specific hazards arising from the chemical (e.g., nature of any hazardous combustion products):

Fire and/or Explosion Hazards: Material will not ignite or burn.

Hazardous Combustion Products: Carbon dioxide, Carbon monoxide

Special protective equipment and precautions for fire-fighters: Will not burn, no special instructions available. Use methods appropriate for surrounding materials.

6. Accidental release measures

Personal precautions, protective equipment, and emergency procedures: Exposure to the spilled material may be severely irritating or toxic. Follow personal protective equipment recommendations found in Section VIII of this MSDS. Personal protective equipment needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits.

Methods and materials for containment and cleaning up: No special spill clean-up considerations. Collect and discard in regular trash.

Safety Data Sheet

Product Name: TUNNEL FOAMING SS 55 GALL

Product identifier: 507255

Revision Date: 08-19-2016

Replaces:

7. Handling and storage

Precautions for safe handling: Toxic or severely irritating material. Avoid contacting and avoid breathing the material. Use only in a well ventilated area. As with all chemicals, good industrial hygiene practices should be followed when handling this material. Avoid contact with material, avoid breathing dusts or fumes, use only in a well ventilated area. Wash thoroughly after handling Do not get in eyes, on skin and clothing Use with adequate ventilation Minimize dust generation and accumulation "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Remove contaminated clothing and wash before reuse

Conditions for safe storage, including any incompatibilities

Conditions for safe storage: No special requirements Limit quantity of material stored. Store in a tightly closed container Store in a cool dry place Keep away from food and drinking water.

Materials to Avoid/Chemical Incompatibility: Strong oxidizing agents Strong acids

8. Exposure controls/personal protection

OSHA permissible exposure limit (PEL), American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value (TLV), and any other exposure limit used or recommended by the chemical manufacturer, importer, or employer preparing the safety data sheet, where available:

Chemical Component	OSHA PEL	ACGIH TLV-TWA	ACGIH STEL
No data available	No data available	No data available	No data available

Appropriate engineering controls: Local exhaust ventilation, process enclosures, or other engineering controls are necessary when handling or using this product to avoid overexposure. Engineering controls must be designed to meet the OSHA chemical specific standard in 29 CFR 1910. Ventilation is required to maintain operator exposure below published exposure limits. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits Facilities storing or using this material should be equipped with an eyewash and safety shower.

Individual protection measures, such as personal protective equipment:

Eye Protection: Wear chemical splash goggles when handling this product. Additionally, wear a face shield when the possibility of splashing of liquid exists. Do not wear contact lenses. Have an eye wash station available. Wear goggles and a Face shield

Skin Protection: Avoid skin contact by wearing chemically resistant gloves, an apron and other protective equipment depending upon conditions of use. Inspect gloves for chemical break-through and replace at regular

Safety Data Sheet

Product Name: TUNNEL FOAMING SS 55 GALL

Product identifier: 507255

Revision Date: 08-19-2016

Replaces:

Respiratory Protection: intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work. Where contact is likely, wear chemical resistant gloves, a chemical suit, rubber boots, and chemical safety goggles plus a face shield
Respiratory protection must be used when handling this product. Use respirators only if ventilation cannot be used to eliminate symptoms or reduce the exposure to below acceptable levels. A supplied air type respirator may be required. Follow a respiratory protection program that meets 29 CFR 1910.134 and ANSI Z88.2 requirements whenever work place conditions warrant the use of a respirator. A supplied air type respiratory will be required.

Other Protective Equipment: Wear goggles and a Face shield Where contact is likely, wear chemical resistant gloves, a chemical suit, rubber boots, and chemical safety goggles plus a face shield

9. Physical and chemical properties

Appearance (physical state, color, etc.):

Appearance (physical state): No data available

Color: No data available

Odor: No data available

Odor threshold: No data available

pH: No data available

Melting Point/Freezing Point (°C): No data available

Initial Boiling Point and Boiling Range (°C): 100

Flash Point (°C): No data available

Evaporation Rate: No data available

Flammability (solid, gas): No data available

Upper/lower flammability or explosive limits:

Upper Flammable/Explosive Limit (%): No data available

Lower Flammable/Explosive Limit (%): No data available

Vapor Pressure: No data available

Vapor Density: No data available

Relative Density: Not determined

Solubility(ies): No data available

Partition coefficient: n-octanol/water: No data available

Auto-ignition Temperature (°C): No data available

Decomposition Temperature: No data available

Viscosity: No data available

Safety Data Sheet

Product Name: TUNNEL FOAMING SS 55 GALL

Product identifier: 507255

Revision Date: 08-19-2016

Replaces:

10. Stability and reactivity

Reactivity:	No data available
Chemical stability:	Stable under normal conditions.
Possibility of hazardous reactions:	No data available
Conditions to avoid (e.g., static discharge, shock, or vibration):	None known.
Incompatible materials:	Strong oxidizing agents Strong acids

11. Toxicological information

Information on the likely routes of exposure (inhalation, ingestion, skin and eye contact):	Inhalation, Ingestion, Skin contact, Eye contact
Symptoms related to the physical, chemical and toxicological characteristics:	No data available

Delayed and immediate effects and also chronic effects from short- and long-term exposure:

Immediate (Acute) Health Effects by Route of Exposure:

Inhalation Irritation:	Can be corrosive to the respiratory tract causing severe irritation and tissue damage. Slightly irritating to the respiratory tract.
Skin Contact:	Corrosive to skin tissue. Can cause chemical burns. May cause skin irritation.
Skin Absorption:	No absorption hazard in normal industrial use.
Eye Contact:	Corrosive to eye tissue. Can cause severe irritation, tearing, and burns that can quickly lead to permanent injury including blindness. Substance causes severe irritation. Permanent eye injury may result.
Ingestion Irritation:	Corrosive to tissue. Can cause severe and permanent damage to mouth, throat, stomach. Aspiration may lead to lung damage. Harmful if swallowed.
Ingestion Toxicity:	Harmful if swallowed. May cause systemic poisoning.

Long-Term (Chronic) Health Effects:

Carcinogenicity:	None of the substances have been shown to cause cancer in long term animal studies. Not a carcinogen according to NTP, IARC, or OSHA.
Reproductive and Developmental Toxicity:	No data available to indicate product or any components present at greater than 0.1% may cause birth defects.
Mutagenicity:	No data available to indicate product or any components present at greater than 0.1% is mutagenic or genotoxic.
Inhalation:	Upon prolonged and/or repeated exposure, can be corrosive to the respiratory tract causing severe irritation and tissue damage.
Skin Contact:	Upon prolonged or repeated contact, corrosive to skin tissue. Can cause chemical burns.
Skin Absorption:	Upon prolonged or repeated exposure, no hazard in normal industrial use.

Safety Data Sheet

Product Name: TUNNEL FOAMING SS 55 GALL

Product identifier: 507255

Revision Date: 08-19-2016

Replaces:

Numerical measures of toxicity (such as acute toxicity estimates)

Component Toxicology Data

Chemical Component	Oral LD50	Dermal LD50	Inhalation LC50
Sodium metasilicate	Oral LD50 Rat 1153 mg/kg		

Whether the hazardous chemical is listed in the National Toxicology Program (NTP) Report on Carcinogens (latest edition) or has been found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs (latest edition), or by OSHA

Chemical Name	OSHA Carcinogen	IARC Carcinogen	NTP Carcinogen
No data available	N	N	N

12. Ecological information

Ecotoxicity (aquatic and terrestrial, where available): This material is not expected to be harmful to the ecology.
Persistence and degradability: No data available
Bioaccumulative potential: No data
Mobility in soil: No data available
Other adverse effects (such as hazardous to the ozone layer): No data available

Ecological Toxicity Data

Chemical Component	Aquatic EC50 Crustacea	Aquatic ERC50 Algae	Aquatic LC50 Fish
No data available			

13. Disposal considerations

Description of waste residues and information on their safe handling and methods of disposal, including the disposal of any contaminated packaging

Description of waste residues: Spent or discarded material is non-hazardous according to environmental regulations.

Waste treatment methods (including packaging): Dispose of in a landfill. Disposal is not likely to be regulated.

14. Transport information

UN number: No data available
UN proper shipping name: Not Regulated
Transport hazard class(es): No data available
Packing group: No data available

Safety Data Sheet

Product Name: TUNNEL FOAMING SS 55 GALL

Product identifier: 507255

Revision Date: 08-19-2016

Replaces:

The shipper is responsible for following all applicable regulations. The transportation classification provided is based on ITW Evercoat original packaging, which is suitable for domestic ground transport only.

15. Regulatory information

Safety, health and environmental regulations specific for the product in question

TSCA Status: All components in this product are on the TSCA Inventory.

Regulated Components

Chemical Component	CAS number and other unique identifiers	CERCLA	SARA EHS	SARA 313	California Prop 65
Sodium hydroxide	1310-73-2	N	N	Y	N

16. Other information, including date of preparation or last revision.

Revision Date: 08-19-2016

Revision Number: 8

Disclaimer: NOTICE: The information accumulated herein is believed to be correct as of the date issued from sources, which are believed to be accurate and reliable. Since it is not possible to anticipate all circumstances of use, recipients are advised to confirm, in advance of need, that the information is current, applicable and suitable to their circumstances