

Revision Date 19-Apr-2016

SAFETY DATA SHEET

Version 5

1. IDENTIFICATION	
Draduct identifier	
Product identifier	
Product Name	765-1485 NAPA BLACK RTV SILICONE (PTX81158) 3 OZ
Other means of identification	
Product Code	21188
Synonyms	None
Recommended use of the chemical	and restrictions on use
Recommended Use	Sealant
Uses advised against	No information available
Details of the supplier of the safety	data sheet
Manufacturer Address	Distributor
ITW Permatex	ITW Permatex Canada
6875 Parkland Blvd.	35 Brownridge Road, Unit 1
Solon, OH 44139 USA	Halton Hills, ON Canada L7G 0C6
	Telephone: (800) 924-6994
Company Phone Number	1-87-Permatex
	(877) 376-2839
24 Hour Emergency Phone Number	
5,	International Emergency:
	00+1+ 813-248-0585
	Contract Number: MIS0003453
E-mail address	mail@permatex.com
Solon, OH 44139 USA Company Phone Number 24 Hour Emergency Phone Number	Halton Hills, ON Canada L7G 0C6 Telephone: (800) 924-6994 1-87-Permatex (877) 376-2839 Chem-Tel: 800-255-3924 International Emergency: 00+1+ 813-248-0585 Contract Number: MIS0003453

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1
Carcinogenicity	Category 2

Label elements

Emergency Overview

Warning

Causes serious eye irritation May cause an allergic skin reaction Suspected of causing cancer

21188 - 765-1485 NAPA BLACK RTV SILICONE (PTX81158) 3 OZ



Physical state Paste

Odor Mild

Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Avoid breathing dust/fume/gas/mist/vapors/spray Contaminated work clothing should not be allowed out of the workplace

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention Specific treatment (see supplemental first aid instructions on this label)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention IF ON SKIN: Wash with plenty of soap and water If skin irritation or rash occurs: Get medical advice/attention Wash contaminated clothing before reuse

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

- Not applicable

Unknown acute toxicity

29.274 % of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

substance(s)

Chemical Name	CAS No	Weight-%	Trade Secret
DISTILLATES (PETROLEUM), HYDROTREATED	64742-47-8	3 - 7	*
LIGHT			
2-BUTANONE OXIME	96-29-7	1 - 5	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice

Get medical advice/attention if you feel unwell.

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical

/attention. SKIN:. Wash with soap and water. If skin irritation or rash occurs: Get medical /attention. Wash contaminated clothing before reuse. ALED: Remove victim to fresh air and keep at rest in a position comfortable for ing. If symptoms persist, call a physician.
/attention. Wash contaminated clothing before reuse. ALED: Remove victim to fresh air and keep at rest in a position comfortable for ing. If symptoms persist, call a physician.
ing. If symptoms persist, call a physician.
ALLOWED:. Do NOT induce vomiting. Never give anything by mouth to an scious person. Call a physician.
ersonal protective equipment as required.
h acute and delayed
ection 2 for more information.
ion and special treatment needed
symptomatically.
5. FIRE-FIGHTING MEASURES
firefighters pparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full
CCIDENTAL RELEASE MEASURES
nt and emergency procedures
e adequate ventilation, especially in confined areas. Avoid contact with eyes and ski ersonal protective equipment as required.
t flush into surface water or sanitary sewer system. See Section 12 for additional jical Information.

Methods for containment	Prevent further leakage or spillage if safe to do so.
Methods for cleaning up	Ensure adequate ventilation. Flood with water to complete polymerization and scrape off floor. Sweep up and shovel into suitable containers for disposal. Slippery, can cause falls if walked on.
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling	Handle in accordance with good industrial hygiene and safety practice. Avoid breathing
	vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling.
	Wash contaminated clothing before reuse. Use personal protective equipment as required.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container tightly closed in a dry and well-ventilated place. Protect from moisture.

Incompatible materials Strong oxidizing agents, Acids, Water

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines . NIOSH IDLH Immediately Dangerous to Life or Health

Other Information	Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962
	(11th Cir., 1992).

Appropriate engineering controls

Engineering Controls	Showers
	Eyewash stations
	Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection	Tight sealing safety goggles.
Skin and body protection	Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.
Respiratory protection	Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate.
General Hygiene Considerations	When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Paste
Appearance	Black
Odor	Mild
Odor threshold	No information available
Property pH Melting point / freezing point Boiling point / boiling range Flash point Evaporation rate Flammability (solid, gas) Flammability Limit in Air Upper flammability limit:	Values No information available No information available Not Applicable > 93 °C / > 200 °F No information available No information available

Remarks • Method

Polymerization Tag Closed Cup

21188 - 765-1485 NAPA BLACK RTV SILICONE (PTX81158) 3 OZ

Lower flammability limit: Vapor pressure Vapor density Relative density Water solubility Solubility in other solvents Partition coefficient Autoignition temperature Decomposition temperature Kinematic viscosity Dynamic viscosity Explosive properties Oxidizing properties Other Information	No information available <5 mm Hg 3.0 1.43 Not applicable No information available No information available
Softening point	No information available
Molecular weight	No information available
VOC Content (%)	3.2%, 45.87 g/l
Density	No information available
Bulk density	No information available

Air = 1

Polymerization

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Excessive heat.

Incompatible materials

Strong oxidizing agents, Acids, Water

Hazardous Decomposition Products

Carbon oxides Nitrogen oxides (NOx) Formaldehyde May release 2-butanone oxime (ethyl methyl ketoxime) at elevated temperature

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation	May cause irritation of respiratory tract.
Eye contact	Contact with eyes may cause irritation. May cause redness and tearing of the eyes.
Skin contact	May cause skin irritation and/or dermatitis. May cause sensitization by skin contact.
Ingestion	Ingestion may cause irritation to mucous membranes.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat)4 h
2-BUTANONE OXIME	= 930 mg/kg (Rat)	= 0.2 mg/kg (Rabbit)	= 20 mg/L (Rat)4 h

96-29-7

Information on toxicological effects

Symptoms

No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure_

Sensitization Germ cell mutagenicity Carcinogenicity	No information available. No information available. The table below indicates whether each agency has listed any ingredient as a carcinogen.
ACGIH (American Conference of Go A3 - Animal Carcinogen	
IARC (International Agency for Res Group 2B - Possibly Carcinogenic to I	Humans
X - Present	alth Administration of the US Department of Labor)
Target Organ Effects	Eyes, Lymphatic System, Respiratory system, Skin.
The following values are calculated ATEmix (oral)	l based on chapter 3.1 of the GHS document . 14090 mg/kg

ATEmix (dermal)

14090 mg/kg 9616 mg/kg

12. ECOLOGICAL INFORMATION

Ecotoxicity

95.074 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
DISTILLATES (PETROLEUM),	-	45: 96 h Pimephales promelas mg/L	4720: 96 h Den-dronereides
HYDROTREATED LIGHT		LC50 flow-through 2.2: 96 h	heteropoda mg/L LC50
64742-47-8		Lepomis macrochirus mg/L LC50	
		static 2.4: 96 h Oncorhynchus	
		mykiss mg/L LC50 static	
2-BUTANONE OXIME	83: 72 h Desmodesmus subspicatus	777 - 914: 96 h Pimephales	750: 48 h Daphnia magna mg/L
96-29-7	mg/L EC50	promelas mg/L LC50 flow-through	EC50
		760: 96 h Poecilia reticulata mg/L	
		LC50 static 320 - 1000: 96 h	
		Leuciscus idus mg/L LC50 static	

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

Chemical Name	Partition coefficient	
2-BUTANONE OXIME	0.65	
96-29-7		

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated packaging

Do not reuse container.

US EPA Waste Number

Not applicable

14. TRANSPORT INFORMATION

DOT Proper shipping name:	Not regulated
IATA Proper shipping name:	Not regulated
IMDG Proper shipping name:	Not regulated

15. REGULATORY INFORMATION

International Inventories	
TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Not Listed.
ENCS	Not Listed.
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances ENCS - Japan Existing and New Chemical Substances IECSC - China Inventory of Existing Chemical Substances KECL - Korean Existing and Evaluated Chemical Substances PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and

Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65	
CARBON BLACK - 1333-86-4	Carcinogen	
SILICA, QUARTZ - 14808-60-7	Carcinogen	

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
LIMESTONE 1317-65-3	X	X	Х
CARBON BLACK 1333-86-4	X	X	Х
SILICA, QUARTZ 14808-60-7	X	X	Х

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

WHMIS Hazard Class

D2B - Toxic materials

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA HMIS Health hazards 2 Health hazards 2 Flammability 1 Flammability 1 Instability 0 Physical hazards 0

Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

Revision Date 19-Apr-2016

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet