

## Car Brite™ Metallic Fallout Remover

Version Revision Date: SDS Number: Date of last issue: 04/29/2018 2.0 09/06/2018 600000000764 Date of first issue: 05/23/2016

## **SECTION 1. IDENTIFICATION**

Product name : CB E038E METALLIC FALLOUT REMOVER BULK

Product code : 691720

Manufacturer or supplier's details

Company name of supplier : Niteo Products, LLC

Address : Dallas TX 75225

Email Address : EHS@niteoproducts.com

Telephone : 1-844-696-4836

Emergency telephone num-

ber

: 1-800-424-9300 / 1-703-741-5970

#### **SECTION 2. HAZARDS IDENTIFICATION**

GHS classification in accordance with 29 CFR 1910.1200

Skin corrosion : Category 1

Serious eye damage : Category 1

**GHS** label elements

Hazard pictograms



Signal word : Danger

Hazard statements : Causes severe skin burns and eye damage.

Precautionary statements : Prevention:

Wash skin thoroughly after handling.

Wear protective gloves/ protective clothing/ eye protection/ face

protection.

Response:

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated

clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing. Immediately call a POISON CENTER/doctor.



# Car Brite™ Metallic Fallout Remover

Version Revision Date: SDS Number: Date of last issue: 04/29/2018 2.0 09/06/2018 600000000764 Date of first issue: 05/23/2016

Wash contaminated clothing before reuse.

Storage:

Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal

plant.

Other hazards

None known.

### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

### **Hazardous components**

Chemical name	CAS-No.	Concentration (% w/w)
Oxalic acid	144-62-7	>= 5 - < 10
Alcohols, C9-11, ethoxylated	68439-46-3	>= 1 - < 3

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

### **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If breathed in, move person into fresh air.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Take off contaminated clothing and shoes immediately.

If on skin, rinse well with water.

Wash contaminated clothing before re-use. If skin irritation persists, call a physician.

In case of eye contact : In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If swallowed : Get medical attention immediately.

Do NOT induce vomiting. Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.



# Car Brite™ Metallic Fallout Remover

Version Revision Date: SDS Number: Date of last issue: 04/29/2018 2.0 09/06/2018 600000000764 Date of first issue: 05/23/2016

Most important symptoms and effects, both acute and delayed

Causes serious eye damage. Causes severe burns.

Notes to physician

This product contains oxalic acid. Following ingestion, inactivate oxalate by giving calcium as a dilute solution of calcium lactate, lime water, finely pulverized chalk, plaster, and/or milk. Gastric lavage is controversial due to possible corrosion in the esophagus or stomach. Systemic effects may be due to formation of a complex between oxalic acid and calcium which is insoluble at physiological pH and can be deposited in the brain and renal tubules, causing nervous system disturbances and kidney damage. Resultant hypocalcemia may be responsible for the muscular and cardiovascular effects, although hypovolemic shock from gastroenteritis or hemorrhage may also cause cardiovascular collapse. Intravenous administration of calcium gluconate or calcium chloride may be required if hypocalcemia or hypocalcemic tetany occur.

### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Water spray

Carbon dioxide (CO2)

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire-

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod-

ucts

Carbon oxides

Specific extinguishing meth-

ods

Product is compatible with standard fire-fighting agents.

Further information : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment :

for firefighters

In the event of fire, wear self-contained breathing apparatus.

### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emer-

gency procedures

Use personal protective equipment.

Avoid breathing dust.

Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Prevent product from entering drains.

Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform



# Car Brite™ Metallic Fallout Remover

Version Revision Date: SDS Number: Date of last issue: 04/29/2018 2.0 09/06/2018 600000000764 Date of first issue: 05/23/2016

respective authorities.

Methods and materials for containment and cleaning up

: Keep in suitable, closed containers for disposal.

### **SECTION 7. HANDLING AND STORAGE**

Advice on protection against :

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling : Do not breathe vapours/dust.

Avoid contact with skin and eyes.

When diluting, always add the product to water. Never add

water to the product.

Dispose of rinse water in accordance with local and national

regulations.

Container hazardous when empty.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

For personal protection see section 8.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Observe label precautions.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Oxalic acid	144-62-7	TWA	1 mg/m3	ACGIH
		STEL	2 mg/m3	ACGIH
		TWA	1 mg/m3	NIOSH REL
		ST	2 mg/m3	NIOSH REL
		TWA	1 mg/m3	OSHA Z-1
		TWA	1 mg/m3	OSHA P0
		STEL	2 mg/m3	OSHA P0

### Hazardous components without workplace control parameters

Components	CAS-No.
Alcohols C9-11 ethoxylated	68439-46-3

**Engineering measures** : Provide sufficient mechanical (general and/or local exhaust)

ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or

apparent adverse effects.

## Personal protective equipment

Hand protection



# Car Brite™ Metallic Fallout Remover

Version Revision Date: SDS Number: Date of last issue: 04/29/2018 2.0 09/06/2018 600000000764 Date of first issue: 05/23/2016

Remarks : Wear resistant gloves (consult your safety equipment suppli-

er). The suitability for a specific workplace should be discussed with the producers of the protective gloves. Discard

gloves that show tears, pinholes, or signs of wear.

Eye protection : Wear chemical splash goggles and face shield when there is

potential for exposure of the eyes or face to liquid, vapor or

mist.

Skin and body protection : Choose body protection according to the amount and con-

centration of the dangerous substance at the work place.

Wear as appropriate: Impervious clothing Safety shoes

Remove and wash contaminated clothing before re-use.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

When using do not smoke. When using do not eat or drink.

### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Colour : colourless

Odour : mild

pH : 0.5

Melting point/freezing point : No data available

Boiling point/boiling range : 100 °C

(1,013 hPa)

The value is calculated

Flash point : Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Self-ignition : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure : 23.3333333 hPa (20 °C)

The value is calculated

Density : 1.027 g/cm3



# Car Brite™ Metallic Fallout Remover

Version Revision Date: SDS Number: Date of last issue: 04/29/2018 09/06/2018 60000000764 Date of first issue: 05/23/2016 2.0

Solubility(ies)

Water solubility soluble

Partition coefficient: n-

octanol/water

No data available

Viscosity

Viscosity, dynamic No data available

Viscosity, kinematic No data available

Oxidizing properties No data available

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity No decomposition if stored and applied as directed.

Chemical stability No decomposition if stored and applied as directed.

Possibility of hazardous reac-

tions

No decomposition if stored and applied as directed.

Hazardous polymerisation does not occur.

Conditions to avoid No data available

Incompatible materials Aluminium

halogens Copper Copper alloys Silver

Strong bases

Strong oxidizing agents

Do not use with aluminum equipment at temperatures above

49C or 120 degrees F.

Hazardous decomposition

products

Carbon oxides

# **SECTION 11. TOXICOLOGICAL INFORMATION**

## Information on likely routes of exposure

Inhalation Skin contact Eye contact Ingestion

### **Acute toxicity**

Not classified based on available information.

### **Product:**

Acute oral toxicity Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

Remarks: Causes digestive tract burns.



# Car Brite™ Metallic Fallout Remover

Version Revision Date: SDS Number: Date of last issue: 04/29/2018 2.0 09/06/2018 600000000764 Date of first issue: 05/23/2016

### **Components:**

Oxalic acid:

Acute oral toxicity : LD50 (Rat): 1,080 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 20,000 mg/kg

Alcohols, C9-11, ethoxylated:

Acute oral toxicity : LD50 (Rat): 500 - 2,000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

Skin corrosion/irritation

Causes severe burns.

**Product:** 

Remarks: Causes severe skin burns and eye damage.

### **Components:**

Oxalic acid:

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

Alcohols, C9-11, ethoxylated:

Result: Mild skin irritation

Serious eye damage/eye irritation

Causes serious eye damage.

**Product:** 

Remarks: May cause irreversible eye damage.

## **Components:**

Oxalic acid:

Result: Irreversible effects on the eye

Alcohols, C9-11, ethoxylated:

Result: Irreversible effects on the eye

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.



# Car Brite™ Metallic Fallout Remover

Version Revision Date: SDS Number: Date of last issue: 04/29/2018 2.0 09/06/2018 600000000764 Date of first issue: 05/23/2016

**Components:** 

Oxalic acid:

Genotoxicity in vitro : Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

Carcinogenicity

Not classified based on available information.

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

**Aspiration toxicity** 

Not classified based on available information.

**Further information** 

**Product:** 

Remarks: No data available

# **SECTION 12. ECOLOGICAL INFORMATION**

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Waste from residues : Dispose of in accordance with all applicable local, state and

federal regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product.

Do not re-use empty containers.



## Car Brite™ Metallic Fallout Remover

Version Revision Date: SDS Number: Date of last issue: 04/29/2018 2.0 09/06/2018 600000000764 Date of first issue: 05/23/2016

### **SECTION 14. TRANSPORT INFORMATION**

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

## International Regulations

**IATA-DGR** 

UN/ID No. : UN 1760

Proper shipping name : Corrosive liquid, n.o.s.

(OXALIC ACID)

Class : 8
Packing group : III
Labels : 8
Packing instruction (cargo : 856

aircraft)

**IMDG-Code** 

UN number : UN 1760

Proper shipping name : CORROSIVE LIQUID, N.O.S.

(OXALIC ACID)

Class : 8
Packing group : III
Labels : 8
EmS Code : F-A, S-B

Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

## **National Regulations**

**49 CFR** 

UN/ID/NA number : UN 1760

Proper shipping name : Corrosive liquids, n.o.s.

(OXALIC ACID)

Class : 8
Packing group : III
Labels : 8
ERG Code : 154
Marine pollutant : no

## **SECTION 15. REGULATORY INFORMATION**

### **EPCRA - Emergency Planning and Community Right-to-Know Act**

### **CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

## SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

# SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.



# Car Brite™ Metallic Fallout Remover

Version Revision Date: SDS Number: Date of last issue: 04/29/2018 2.0 09/06/2018 600000000764 Date of first issue: 05/23/2016

SARA 311/312 Hazards : Skin corrosion or irritation

Serious eye damage or eye irritation

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.


## California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

#### **SECTION 16. OTHER INFORMATION**

#### **Further information**

### NFPA:



Special hazard.

Revision Date : 09/06/2018

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN